



P3MPB015

## 20V P-Channel MOSFETs

## General Description


These P-Channel enhancement mode power field effect transistors are using trench DMOS technology. This advanced technology has been especially tailored to minimize on-state resistance, provide superior switching performance, and withstand high energy pulse in the avalanche and commutation mode. These devices are well suited for high efficiency fast switching applications.

| $BV_{DSS}$ | $R_{DS(ON)}$ | $I_D$ |
|------------|--------------|-------|
| -20 V      | 15 mΩ        | -26 A |

## Features

- $R_{DS(ON)} \leq 15\text{m}\Omega @ V_{GS} = -4.5\text{V}$
- Fast switching
- Green Device Available
- Suit for -1.8V Gate Drive Applications
- Improved dv/dt capability

PPAK3X3 Pin Configuration



## Applications

- Notebook
- Networking
- Hand-Held Instruments
- Load Switch

Absolute Maximum Ratings  $T_C=25^\circ\text{C}$  unless otherwise noted

| Symbol       | Parameter  | Rating         | Units                     |
|--------------|--|----------------|---------------------------|
| $V_{DS}$     | Drain-Source Voltage                                   | -20            | V                         |
| $V_{GS}$     | Gate-Source Voltage                                    | $\pm 10$       | V                         |
| $I_D$        | Drain Current - Continuous ( $T_C=25^\circ\text{C}$ )  | -26            | A                         |
|              | Drain Current - Continuous ( $T_C=100^\circ\text{C}$ ) | -14            | A                         |
| $I_{DM}$     | Drain Current - Pulsed (NOTE 1)                        | -104           | A                         |
| $P_D$        | Power Dissipation ( $T_C=25^\circ\text{C}$ )           | 44             | W                         |
|              | Power Dissipation - Derate above $25^\circ\text{C}$    | 0.36           | $\text{W}/^\circ\text{C}$ |
| $T_J$        | Operating Junction Temperature Range                   | -55 to 150     | $^\circ\text{C}$          |
| $T_{STG}$    | Storage Temperature Range                              | -55 to 150     | $^\circ\text{C}$          |
| Marking Code |  | PB015 , DC2305 |                           |

## Thermal Characteristics

| Symbol          | Parameter                              | Typ. | Max. | Unit                      |
|-----------------|--|------|------|---------------------------|
| $R_{\theta JA}$ | Thermal Resistance Junction to Ambient | ---  | 50   | $^\circ\text{C}/\text{W}$ |
| $R_{\theta JC}$ | Thermal Resistance Junction to Case    | ---  | 2.8  | $^\circ\text{C}/\text{W}$ |



P3MPB015

RoHS

20V P-Channel MOSFETs

**Electrical Characteristics ( $T_J=25^\circ\text{C}$ , unless otherwise noted)****Off Characteristics**

| Symbol                   | Parameter                      | Conditions  | Min. | Typ. | Max.      | Unit          |
|--------------------------|--------------------------------|---|------|------|-----------|---------------|
| $\text{BV}_{\text{DSS}}$ | Drain-Source Breakdown Voltage | $V_{\text{GS}}=0\text{V}$ , $I_D = -250\mu\text{A}$                                     | -20  | ---  | ---       | V             |
| $I_{\text{DSS}}$         | Drain-Source Leakage Current   | $V_{\text{DS}} = -20\text{V}$ , $V_{\text{GS}} = 0\text{V}$ , $T_J = 25^\circ\text{C}$  | ---  | ---  | -1        | $\mu\text{A}$ |
|                          |                                | $V_{\text{DS}} = -16\text{V}$ , $V_{\text{GS}} = 0\text{V}$ , $T_J = 125^\circ\text{C}$ | ---  | ---  | -10       | $\mu\text{A}$ |
| $I_{\text{GSS}}$         | Gate-Source Leakage Current    | $V_{\text{GS}} = \pm 10\text{V}$ , $V_{\text{DS}} = 0\text{V}$                          | ---  | ---  | $\pm 100$ | $\text{nA}$   |

**On Characteristics**

| Symbol              | Parameter                         | Conditions  | Min. | Typ. | Max. | Unit             |
|---------------------|-----------------------------------|---|------|------|------|------------------|
| $R_{\text{DS(ON)}}$ | Static Drain-Source On-Resistance | $V_{\text{GS}} = -4.5\text{V}$ , $I_D = -6\text{A}$       | ---  | 12   | 15   | $\text{m}\Omega$ |
|                     |                                   | $V_{\text{GS}} = -2.5\text{V}$ , $I_D = -4\text{A}$       | ---  | 15   | 20   |                  |
|                     |                                   | $V_{\text{GS}} = -1.8\text{V}$ , $I_D = -3\text{A}$       | ---  | 20   | 26   |                  |
| $V_{\text{GS(th)}}$ | Gate Threshold Voltage            | $V_{\text{GS}} = V_{\text{DS}}$ , $I_D = -250\mu\text{A}$ | -0.3 | -0.6 | -1.0 | V                |
| $g_{\text{fs}}$     | Forward Transconductance          | $V_{\text{DS}} = -10\text{V}$ , $I_S = -6\text{A}$        | ---  | 20   | ---  | S                |

**Dynamic and switching Characteristics**

| Symbol              | Parameter                    | Conditions  | Min. | Typ. | Max. | Unit |
|---------------------|------------------------------|---|------|------|------|------|
| $Q_g$               | Total Gate Charge            | $V_{\text{DS}} = -10\text{V}$ , $V_{\text{GS}} = -4.5\text{V}$ , $I_D = -6\text{A}$ (NOTE 2、3)                    | ---  | 27   | 40   | nC   |
| $Q_{\text{gs}}$     | Gate-Source Charge           |   | ---  | 2.4  | 4.8  |      |
| $Q_{\text{gd}}$     | Gate-Drain Charge            |   | ---  | 5.3  | 8    |      |
| $T_{\text{d(on)}}$  | Turn-On Delay Time           | $V_{\text{DD}} = -10\text{V}$ , $V_{\text{GS}} = -4.5\text{V}$ , $R_G = 25\Omega$ , $I_D = -1\text{A}$ (NOTE 2、3) | ---  | 16.2 | 31   | nS   |
| $T_r$               | Rise Time                    |   | ---  | 43.5 | 83   |      |
| $T_{\text{d(off)}}$ | Turn-Off Delay Time          |   | ---  | 114  | 217  |      |
| $T_f$               | Fall Time                    |   | ---  | 28.8 | 55   |      |
| $C_{\text{iss}}$    | Input Capacitance            |   | ---  | 2320 | 3370 | pF   |
| $C_{\text{oss}}$    | Output Capacitance           | $V_{\text{DS}} = -15\text{V}$ , $V_{\text{GS}} = 0\text{V}$ , $F = 1\text{MHz}$                                   | ---  | 280  | 410  |      |
| $C_{\text{rss}}$    | Reverse Transfer Capacitance |   | ---  | 175  | 260  |      |

**Drain-Source Diode Characteristics and Ratings**

| Symbol          | Parameter                 | Conditions  | Min. | Typ. | Max. | Unit |
|-----------------|---------------------------|---|------|------|------|------|
| $I_s$           | Continuous Source Current | $V_G = V_D = 0\text{V}$ , Force Current                                     | ---  | ---  | -11  | A    |
| $I_{\text{SM}}$ | Pulsed Source Current     |   | ---  | ---  | -44  | A    |
| $V_{\text{SD}}$ | Diode Forward Voltage     | $V_{\text{GS}} = 0\text{V}$ , $I_s = -1\text{A}$ , $T_J = 25^\circ\text{C}$ | ---  | ---  | -1   | V    |

## NOTES :

1. Repetitive Rating : Pulsed width limited by maximum junction temperature.
2. The data tested by pulsed, pulse width  $\leq 300\mu\text{s}$ , duty cycle  $\leq 2\%$ .
3. Essentially independent of operating temperature.




**P3MPB015**


Pb RoHS

**20V P-Channel MOSFETs**


### Characteristics Curves




**Fig.1 Continuous Drain Current vs.  $T_c$**




**Fig.2 Normalized RDSON vs.  $T_j$**




**Fig.3 Normalized  $V_{th}$  vs.  $T_j$**



**Fig.4 Gate Charge Waveform**



**Fig.5 Normalized Transient Response**



**Fig.6 Maximum Safe Operation Area**



P3MPB015

Pb RoHS

20V P-Channel MOSFETs

### Characteristics Curves






Fig.7 Switching Time Waveform

Fig.8 Gate Charge Waveform

### Package Outline Dimensions



PPAK3X3

Dimensions in inches and (millimeters)



## LEGAL DISCLAIMER

- The product is provided "AS IS" without any guarantees or warranty. In association with the product, Eris Technology Corporation, its affiliates, and their directors, officers, employees, agents, successors and assigns (collectively, the "Eris") makes no warranties of any kind, either express or implied, including but not limited to warranties of merchantability, fitness for a particular purpose, of title, or of non-infringement of third party rights.
- The information in this document and any product described herein are subject to change without notice and should not be construed as a commitment by Eris. Eris assumes no responsibility for any errors that may appear in this document.
- Eris does not assume any liability arising out of the application or use of this document or any product described herein, any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Eris and all the companies whose products are represented on Eris website, harmless against all damages.
- No license, express or implied, by estoppels or otherwise, to any intellectual property is granted by this document or by any conduct of Eris. Product name and markings notes herein may be trademarks of their respective owners.
- Eris does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel.
- Should Customers purchase or use Eris products for any unintended or unauthorized application, Customers shall indemnify and hold Eris and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.
- The official text is written in English and the English version of this document is the only version endorsed by Eris. Any discrepancies or differences created in the translations are not binding and have no legal effect on Eris for compliance or enforcement purposes.