



20V N-Channel MOSFETs

General Description



These N-Channel enhancement mode power field effect transistors are using trench DMOS technology. This advanced technology has been especially tailored to minimize on-state resistance, provide superior switching performance, and withstand high energy pulse in the avalanche and commutation mode. These devices are well suited for high efficiency fast switching applications.

BV_{DSS}	$R_{DS(ON)}$	I_D
20 V	230 m Ω	0.98 A

Features

- $R_{DS(ON)} \leq 230m\Omega @ V_{GS}=4.5V$
- Improved dv/dt Capability
- Fast Switching
- Green Device Available
- ESD Protection

SOT-23 Pin Configuration



Applications

- Power Management in DC/DC Converters
- Power Load Switch
- Notebook Battery Management

Absolute Maximum Ratings $T_J=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Value	Units
V_{DS}	Drain-Source Voltage	20	V
V_{GS}	Gate-Source Voltage	± 12	V
I_D	Drain Current - Continuous ($T_A=25^\circ\text{C}$)	0.98	A
I_{DM}	Drain Current - Pulsed ($T_A=25^\circ\text{C}$) (NOTE 1)	1.8	A
P_D	Power Dissipation ($T_A=25^\circ\text{C}$)	0.36	W
T_J	Operating Junction Temperature Range	-55 to 150	$^\circ\text{C}$
T_{STG}	Storage Temperature Range	-55 to 150	$^\circ\text{C}$
Marking Code		06	

Thermal Characteristics

Symbol	Parameter	Value	Unit
$R_{\theta JA}$	Thermal Resistance Junction to Ambient	350	$^\circ\text{C/W}$



20V N-Channel MOSFETs

Electrical Characteristics (T_a=25°C, unless otherwise noted)

Off Characteristics

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _D =250uA	20	---	---	V
I _{DSS}	Drain-Source Leakage Current	V _{DS} =16V, V _{GS} =0V	---	---	1	uA
I _{GSS}	Gate-Source Leakage Current	V _{GS} =±12V, V _{DS} =0V	---	---	±10	uA

On Characteristics

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
R _{DS(ON)}	Static Drain-Source On-Resistance	V _{GS} =4.5V, I _D =0.55A	---	---	230	mΩ
		V _{GS} =2.5V, I _D =0.45A	---	---	330	
		V _{GS} =1.8V, I _D =0.35A	---	---	550	
V _{GS(th)}	Gate Threshold Voltage	V _{GS} =V _{DS} , I _D =250uA	0.5	---	1.0	V
g _{fs}	Forward Transconductance	V _{DS} =5V, I _D =0.55A	---	1.8	---	S

Dynamic and switching Characteristics (NOTE 3)

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
Q _g	Total Gate Charge	V _{DS} =10V, V _{GS} =4.5V, I _D =1A	---	1	---	nC
Q _{gs}	Gate-Source Charge		---	0.3	---	
Q _{gd}	Gate-Drain Charge		---	0.1	---	
T _{d(on)}	Turn-On Delay Time	V _{DS} =10V, V _{GS} =4.5V, R _{GEN} =6Ω, I _D =2A	---	1.2	---	ns
T _r	Rise Time		---	24.7	---	
T _{d(off)}	Turn-Off Delay Time		---	13.6	---	
T _f	Fall Time		---	14.8	---	
C _{iss}	Input Capacitance	V _{DS} =10V, V _{GS} =0V, f=1MHz	---	41	---	pF
C _{oss}	Output Capacitance		---	17	---	
C _{rss}	Reverse Transfer Capacitance		---	10	---	
R _g	Gate Resistance	V _{GS} =0V, V _{DS} =0V, F=1MHz	---	198	---	Ω

Drain-Source Diode Characteristics and Ratings

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
V _{SD}	Diode Forward Voltage	V _{GS} =0V, I _S =1A	---	---	1.1	V

NOTES :

1. Repetitive Rating : Pulsed width limited by maximum junction temperature.
2. The data tested by pulsed , pulse width ≤ 300us , duty cycle ≤ 2%.
3. Guaranteed by design, not subject to product.



Characteristics Curves

FIG. 1-Drain Current




FIG. 2-Gate Threshold Voltage




FIG. 3-Drain-Source On-Resistance




FIG. 4-Gate Charge Characteristics




FIG. 5-RθJA Transient Thermal Impedance








FIG. 6-Safe Operating Area





Package Outline Dimensions



SOT-23

Dimensions in inches and (millimeters)



LEGAL DISCLAIMER

- The product is provided “AS IS” without any guarantees or warranty. In association with the product, Eris Technology Corporation, its affiliates, and their directors, officers, employees, agents, successors and assigns (collectively, the “Eris”) makes no warranties of any kind, either express or implied, including but not limited to warranties of merchantability, fitness for a particular purpose, of title, or of non-infringement of third party rights.
- The information in this document and any product described herein are subject to change without notice and should not be construed as a commitment by Eris. Eris assumes no responsibility for any errors that may appear in this document.
- Eris does not assume any liability arising out of the application or use of this document or any product described herein, any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Eris and all the companies whose products are represented on Eris website, harmless against all damages.
- No license, express or implied, by estoppels or otherwise, to any intellectual property is granted by this document or by any conduct of Eris. Product name and markings notes herein may be trademarks of their respective owners.
- Eris does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel.
- Should Customers purchase or use Eris products for any unintended or unauthorized application, Customers shall indemnify and hold Eris and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.
- The official text is written in English and the English version of this document is the only version endorsed by Eris. Any discrepancies or differences created in the translations are not binding and have no legal effect on Eris for compliance or enforcement purposes.