

SENCITY® Urban 200

1399.17.0272

Properties

- High Gain Directional antenna for Cellular bands between 3300 MHz and 4200 MHz
- Gain of 11 dBi with dual slant +/-45° polarisation
- Half power beamwidth of 70° (vertical) and 35° (Horizontal)
- Wall bracket is included. Pole bracket is sold as separate item (9091.99.0274)
- N female connector

**Electrical bands**

	Band 1	Band 2
Frequency (MHz)	3300 MHz ... 3800 MHz	3800 MHz ... 4200 MHz
Impedance	50 Ω	50 Ω
VSWR	1.8	1.8
Gain (dBi)	11 dBi	11 dBi
Halfp Beamwidth vertical	35 °	35 °
Halfp Beamwidth horizontal	70 °	70 °
Isolation between Ports	23 dB	22 dB
Vertical Electrical Tilt	0 °	0 °
Front to back ratio	20 dB	20 dB
Ambient Temperature	25 °C	25 °C
Composite Power max	95 W	
Gain [dBic]	11 dBic	11 dBic
Co/Crosspolar Ratio	15 dB	

Ports

	Port 1	Port 2	Port 3	Port 4
Port name		Port 2	Port 3	Port 4
Connector	N, jack (female)	N, jack (female)	N, jack (female)	N, jack (female)
Polarization	-45° slant	+45° slant	-45° slant	+45° slant
DC grounded	No	No	No	

SENCITY® Urban 200

1399.17.0272

Connections				
Port number	Port 1	Port 2	Port 3	Port 4
Band 1	✓	✓	✓	✓
Band 2	✓	✓	✓	✓

Mechanical data	
Dimensions	184.8 mm x 164.6 mm x 84.2 mm (Height x Width x Depth)

Interface and material data	
Radome material	PC (Polycarbonate)
Radome colour	RAL 7035 (light gray)

Environmental data	
Operation temperature	-40 °C ... 70 °C
Storage temperature	-40 °C ... 70 °C
Environment (application)	Indoor/Outdoor
Ingress protection (IP Rating)	IP66
Flammability rating	UL 94-V0

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P35382 / Date of publication: 12.12.2023 / uncontrolled copy