

SENCITY® Road MIMO

1399.99.0118

Properties

- Rugged vehicle rooftop multi-band antenna for heavy duty vehicles like bus and truck
- Supports 2G/3G/4G/5G cellular, Wifi 2.4/5 GHz, Wifi 6E and GNSS (Beidou, Galileo, GPS, Glonass).
- 5 separate ports for 2x2 cellular MIMO and 2x2 Wifi MIMO plus GNSS.
- Single hole mounting, easy cabling feed-through.

**Electrical bands**

	Band 1	Band 2	Band 3	Band 4
Frequency (MHz)	694 MHz ... 790 MHz	790 MHz ... 960 MHz	1710 MHz ... 2400 MHz	2400 MHz ... 2500 MHz
Impedance	50 Ω	50 Ω	50 Ω	50 Ω
VSWR	1.8	1.7	1.7	2
Gain (dBi)	4 dBi	4 dBi	5 dBi	6 dBi
Isolation between Ports	10 dB	10 dB	12 dB	10 dB
Ambient Temperature	25 °C	25 °C	25 °C	25 °C
Composite Power max	40 W	40 W	40 W	40 W

	Band 5	Band 6	Band 7	GNSS
Frequency (MHz)	2400 MHz ... 2690 MHz	3400 MHz ... 3800 MHz	4900 MHz ... 7125 MHz	1559 MHz ... 1610 MHz
Impedance	50 Ω	50 Ω	50 Ω	50 Ω
VSWR	2	1.7	1.8	1.8
Gain (dBi)	5.5 dBi	6 dBi	7 dBi	
Isolation between Ports	22 dB	20 dB	25 dB	
Ambient Temperature	25 °C	25 °C	25 °C	25 °C
Composite Power max	40 W	30 W	30 W	

SENCITY® Road MIMO

1399.99.0118

Electrical remarks

Remarks	Ground plane: Indicated VSWR values are valid for a metallic ground plane of 0.5 x 0.5m or larger and Isolation is provided as typical values. Indicated VSWR values are mostly valid for installations on non-metallic surfaces also (no specific ground plane requirements), apart from VSWR 2.5 below 840 MHz and VSWR 3 below 750 MHz. Indicated gain values will be achieved on a metallic ground plane of 1 x 1 m or larger. Port 2,3 performance in Band 6 is given with typical values of VSWR 1.7 only.
---------	---

Ports

	Cell 1	Cell 2	WiFi 1	WiFi 2
Connector		SMA, plug (male)	SMA, jack (female)	SMA, jack (female)
Cable type	ENVIROFLEX_316_D -AM	ENVIROFLEX_316_D -AM	ENVIROFLEX_316_D -AM	ENVIROFLEX_316_D -AM
Cable length	0.15 m	0.21 m	0.22 m	0.28 m
Polarization	vertical	vertical	vertical	vertical
DC grounded	No	No	No	No

GNSS

Connector	TNC, plug (male)
Cable type	ENVIROFLEX_316_D -AM
Cable length	0.26 m
Polarization	circular right
DC grounded	No

Connections

Port number	Cell 1	Cell 2	WiFi 1	WiFi 2	GNSS
Band 1	✓	✓			
Band 2	✓	✓			
Band 3	✓	✓			
Band 4			✓	✓	
Band 5	✓	✓			
Band 6	✓	✓	✓	✓	
Band 7	✓	✓	✓	✓	
Band 8					✓

Mechanical data

Weight	0.5 kg
Dimensions	98 mm x 83 mm x 208 mm (Height x Width x Depth)
Remarks	Mounting breakthrough Ø30mm

Interface and material data

Radome material	ASA (acrylic ester-styrene-acrylonitrile)
Radome colour	RAL 7043 (dark grey)
Back plate/base plate material	Aluminium

SENCITY® Road MIMO

1399.99.0118

Environmental data	
Operation temperature	-40 °C ... 85 °C
Storage temperature	-40 °C ... 85 °C
Transport temperature	-40 °C ... 85 °C
Ingress protection (IP Rating)	IP68, IP69
Flammability rating	ECE-R118
Solar radiation	DIN 75220

Environmental remarks

Environmental tests: ISO 16750:2010
Low corrosion designed acc. to MIL-F-14072D
ECE-R10
E-Mark
CE-Mark

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P31255 / Date of publication: 17.01.2024 / uncontrolled copy