


## Field mountable, 50 Ohm, 18 GHz, 200°C, ø3.75 mm, FEP jacket EACON\_2C

### Properties

- Field mountable microwave cable designed for assembly in tight spaces
- Excellent performance up to 18 GHz
- 2 piece solderless connectors for easy assembly and re-assembly in the field
- Waterproof IP67 rated



Construction			
Component	Material	Detail	Diameter
Centre conductor	Copper, Silver plated	Wire	0.81 mm
Dielectric	PTFE-LD		2.4 mm
Outer conductor	Copper, Silver plated	Wrapped foil, 100%	2.65 mm
Outer conductor	Copper, Silver plated	Braid	3.35 mm
Jacket	FEP (Fluorinated ethylene propylene)	White	3.75 mm

Electrical data	
Impedance	50 Ω
Operating frequency	≤ 18 GHz
Capacitance	87 pF/m
Velocity of signal propagation	77 %
Signal delay	4.3 ns/m
Screening effectiveness	90 dB at frequency 0.1 GHz ... 18GHz
Insulation resistance	100000000 MΩ*m
Operating Voltage (at sea level)	≤ 1.4 kVrms

Mechanical data	
Weight	approx. 39 g/m
Static bending radius	≥ 12 mm
Dynamic bending radius	< 20 mm

**Field mountable, 50 Ohm, 18 GHz, 200°C, ø3.75 mm, FEP jacket**

EACON\_2C

Environmental data	
Operation temperature	-55 °C ... 200 °C
Flame propagation standard	FAR 25.869
Fire characteristics	contains halogene

Suitable connectors	
Cable group	U92

Ordering information		
Item number	Item description	Available as assembly only
84116378	EACON_2C	No

Power Matrix			
Calculation: typical Attenuation [ formula: (a*f^0.5 + b*f) ] and maximum Power CW [ formula: (p/f^0.5) ]			
a coefficient typical =	<b>0.37</b>	b coefficient typical =	<b>0.0071</b>
fmax =	<b>18</b>	P at 1 GHz =	<b>394</b>
<b>Frequency</b>	<b>Nom. attenuation</b>	<b>Nom. attenuation</b>	<b>CW power</b>
<b>GHz</b>	<b>(dB/m)</b>	<b>(dB/ft)</b>	<b>(W)</b>
	sea level 25°C ambient temperature	sea level 25°C ambient temperature	sea level 40°C ambient temperature
0.20	0.167	0.051	881
0.40	0.237	0.072	623
0.60	0.291	0.089	509
0.80	0.337	0.103	441
1.00	0.377	0.115	394
1.20	0.414	0.126	360
1.40	0.448	0.136	333
1.60	0.479	0.146	311
1.80	0.509	0.155	294
2.00	0.537	0.164	279
4.00	0.768	0.234	197
6.00	0.949	0.289	161
8.00	1.103	0.336	139
10.00	1.241	0.378	125
18.00	1.698	0.517	93

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.  
DOCUMENT PIM-P1126 / Date of publication: 08.08.2024 / uncontrolled copy