

SENCITY® SC Panel

852627

Properties

- 2-Port Panel Antenna
- Frequency Range 380-500 MHz
- Dual Polarization (X-Pol)
- Half-power Beam Width 65°
- Gain 15 dBi



Electrical bands		
	Band 1	Band 2
Frequency (MHz)	380 MHz ... 430 MHz	430 MHz ... 500 MHz
Impedance		50 Ω
VSWR	1.5	1.5
Gain (dBi)	14.5 dBi	15 dBi
Halfp Beamwidth vertical	18 °	18 °
Halfp Beamwidth horizontal	65 °	65 °
Isolation between Ports	30 dB	30 dB
Front to back ratio	25 dB	25 dB
Ambient Temperature	50 °C	50 °C
Composite Power max	500 W	500 W

Ports		
	Port 1	Port 2
Port name	-45°	+ 45
Connector	7/16, jack (female)	7/16, jack (female)
Polarization	-45° slant	+45° slant
DC grounded	Yes	Yes

Connections		
Port number	Port 1	Port 2
Band 1	✓	✓
Band 2	✓	✓

SENCITY® SC Panel

852627

Mechanical data	
Weight	19 kg
Dimensions	2000 mm x 492 mm x 190 mm (Height x Width x Depth)
Remarks	Windload frontal: 1100 N at 150 km/h, lateral: 440 N at 150 km/h , Wind speed survival: 200 km/h
	Packing size (mm): 2080x523x252
	Grounding: The metal parts of the antenna including the mounting kit and the inner conductors are DC grounded.
	Ice protection: Due to the very sturdy antenna construction and the protection of the radiating system by the radome, the antenna remains operational even under icy conditions.
	Material: Reflector screen: Weather-proof aluminum.

Interface and material data	
Radome material	Glass Reinforced Plastic (GRP)
Radome colour	Grey
Back plate/base plate material	Aluminium
Back plate/base plate colour	Grey

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P35398 / Date of publication: 23.01.2024 / uncontrolled copy