

SENCITY® SC Omni

K862232

Properties

- Omni-directional Antenna
- Frequency Range 406-470 MHz
- Vertical Polarization
- Gain 2dBi



Electrical bands	
	Band 1
Frequency (MHz)	406 MHz ... 470 MHz
Impedance	50 Ω
VSWR	1.5
Gain (dBi)	2 dBi
Ambient Temperature	50 °C
Composite Power max	100 W

Electrical remarks	
Remarks	IMD level -150 dBc at carrier power 2x 37dBm

Ports	
	Port 1
Connector	N, jack (female)
Polarization	vertical
DC grounded	Yes

Connections	
Port number	Port 1
Band 1	<input checked="" type="checkbox"/>

SENCITY® SC Omni

K862232

Mechanical data	
Weight	0.8 kg
Dimensions	515 mm (Depth)
Remarks	Windload frontal: 20 N at 150 km/h , Wind speed survival: km/h
	Packing size (mm): 112x97x614
	<p>Mounting: The antenna can be attached in two ways with the supplied mounting kit:</p> <ol style="list-style-type: none"> 1. On the tip of a tubular mast of 40-54 mm diameter (connecting cable runs inside the mast). 2. Laterally at the tip of a tubular mast of 20-54 mm diameter (connecting cable runs outside the mast). <p>Grounding: All metal parts of the antenna including the mounting kit are DC grounded.</p>

Interface and material data	
Radome colour	Grey
Back plate/base plate material	Aluminium
Back plate/base plate colour	Grey

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P31261 / Date of publication: 17.01.2024 / uncontrolled copy