

CONFIDENTIAL

VERTRAULICH

THIS DRAWING IS THE EXCLUSIVE PROPERTY OF MARQUARDT. WITHOUT THEIR CONSENT IT MAY NOT BE REPRODUCED OR GIVEN TO THIRD PARTIES.

Alle Rechte bei Marquardt, auch fuer den Fall von Schutzrechtsanmeldungen. Jede Verfuugungsbezugnis, wie Kopier- und Weitergaberecht, bei uns.

	1	2	3	4	
A	recommended cut-out for snap-in fixing (edge opposite to snap-in direction)		wall thickness	length of cut-out	width of cut-out
			0.75 to 1.25	30.0 -0.1	11 +0.1
			1.25 to 2	30.2 -0.1	11 +0.1
		2 to 3	30.6 -0.1	11 +0.1	

Top view dimensions: 27.2, 9.5, 6.4, R

Side view dimensions: 11 ± 0.1, 16.35, 27, terminal 6.3-0.8

Front view dimensions: 31.5, 14, R1, white

Marking:

Ⓜ
1831.
10(8)/250~5E4
20(4)/250~ T105/55
5/120A 250V~

16A 125-250V AC
1/3HP 125V AC
1 HP 250V AC
R11

Code of manufacture: place/year/week
On box: G

SPST
Suitable for appliances of class II
G=matching IEC 60335-1:2001 clause 30

-	-	-	1831.3311-XX
Figure	Type	Customer Part No.	Art.No.-PI
Shape and location 	Angle ± 2°	Sheet 01	Ident. K
	Edge tolerance	Format DIN A4	Document number 18313311
	Length	Projection	Index d
	Radii	Scale 1:1	Appliance Switch
		All dimensions are in millimetres	
d	138244	2021-10-19	MATHPATIR
c	48427	2006-07-19	HHE
b	47099	2006-04-18	HHE
a	23781	1996-01-30	GRH
Index	MEC-No.	Date (YYYY-MM-DD)	Edited by
		System NX V1872	
		Replacement of Zg.gl.Nr.v.19.11.1991	