

PRODUCT-DETAILS

TY232MX CABLE TIE 18LB 8IN UV BLACK NYLON



General Information	
Extended Product Type	TY232MX
Product ID	7TAG009040R0007
EAN	5414363061540
Catalog Description	CABLE TIE 18LB 8IN UV BLACK NYLON
Long Description	Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to 105 Degrees Celsius (221 F), Weather and Ultraviolet Resistant for Indoor and Outdoor Applications, Length of 203.2mm (8.0 Inches), Width of 2.3mm (0.09 Inches), Tensile Strength Rating of 80 Newtons (18 Pounds), Bulk Pack
Ordering	
E-Number (Finland)	1370011
EAN	5414363061540
UPC	786210884172
Country of Origin	United States (US)
Selling Unit of Measure	each
Dimensions	
Product Net Width	0.09 in 2.3 mm
Product Net Depth / Length	8 in 202 mm

© 2024 ABB. All rights reserved.

2024/04/03

Subject to change without notice

Container Information	
Package Level 1 Units	1000 EA
Package Level 1 Width	304.8 mm 12 ir
Package Level 1 Height	0 mm 0 ir
Package Level 1 Depth / Length	381 mm 15 ir
Package Level 2 Units	10000 EA
Package Level 2 Width	289.56 mm 11.4 ir
Package Level 2 Height	289.56 mm 11.4 ir
Package Level 2 Depth / Length	347.98 mm 13.7 ir
Package Level 3 Units	440000 EA
Package Level 3 Width	0.025 mm 0.001 ir
Package Level 3 Height	0.025 mm 0.001 ir
Package Level 3 Depth / Length	0.025 mm 0.001 ir
	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Environmental RoHS Status Technical UL/CSA	
RoHS Status Technical UL/CSA Flammability According to	
RoHS Status Technical UL/CSA Flammability According to UL94	
RoHS Status Technical UL/CSA Flammability According to UL94 Additional Information	V-2
RoHS Status Technical UL/CSA Flammability According to UL94 Additional Information Brand / Label	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 V-2 Ty-Rag 0.06 to 2.01 ir 1.5 to 51 mr
RoHS Status Technical UL/CSA Flammability According to UL94 Additional Information Brand / Label Bundle Diameter Color	V-2 Ty-Rag 0.06 to 2.01 ir 1.5 to 51 mm Black
RoHS Status Technical UL/CSA Flammability According to UL94 Additional Information Brand / Label Bundle Diameter Color Effective Date	V-2 Ty-Rap 0.06 to 2.01 ir 1.5 to 51 mm Blact 19710324
RoHS Status Technical UL/CSA Flammability According to UL94 Additional Information Brand / Label Bundle Diameter Color Effective Date Lock Type	V-2 Ty-Rap 0.06 to 2.01 ir 1.5 to 51 mm Blact 19710324 Stainless Steel Bart
RoHS Status Technical UL/CSA Flammability According to JL94 Additional Information Brand / Label Bundle Diameter Color Effective Date Lock Type Material	V-2 Ty-Rap 0.06 to 2.01 ir 1.5 to 51 mn Blact 19710324 Stainless Steel Bart Nylon/Polyamide 6.6
RoHS Status Technical UL/CSA Flammability According to UL94 Additional Information Brand / Label Bundle Diameter Color Effective Date Lock Type Material Product Name	V-2 Ty-Rag 0.06 to 2.01 ir 1.5 to 51 mm Black 19710324 Stainless Steel Bart Nylon/Polyamide 6.6 Other /note: See 9903.88.66 and 9903.88. 67
RoHS Status Technical UL/CSA Flammability According to UL94 Additional Information Brand / Label Bundle Diameter Color Effective Date Lock Type Material Product Name Product Type	V-2 Ty-Rap 0.06 to 2.01 ir 1.5 to 51 mr Black 19710324 Stainless Steel Bart Nylon/Polyamide 6.6 Other /note: See 9903.88.66 and 9903.88.67 High Performance
RoHS Status Technical UL/CSA Flammability According to UL94 Additional Information Brand / Label Bundle Diameter Color Effective Date Lock Type Material Product Name Product Type	V-2 Ty-Rag 0.06 to 2.01 ir 1.5 to 51 mm Blac 19710324 Stainless Steel Bart Nylon/Polyamide 6.6 Other /note: See 9903.88.66 and 9903.88.67 High Performance Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures
RoHS Status Technical UL/CSA Flammability According to UL94 Additional Information Brand / Label Bundle Diameter Color Effective Date Lock Type Material Product Name Product Type Special Functions	V-2 Ty-Rag 0.06 to 2.01 ir 1.5 to 51 mm Black 19710324 Stainless Steel Bart Nylon/Polyamide 6.6 Other /note: See 9903.88.66 and 9903.88. 67
RoHS Status	V-2 Ty-Rag 0.06 to 2.01 ir 1.5 to 51 mr Black 19710324 Stainless Steel Bart Nylon/Polyamide 6.6 Other /note: See 9903.88.66 and 9903.88.67 High Performance Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time

Certificates and Declarations			
Data Sheet, Technical Information		TDS000570	
Declaration of Conformity		9AKK107492A9841	
© 2024 ABB. All rights reserved.	2024/04/03	Subject to change	

Subject to change without notice

Classifications		
ETIM 6	EC000046 - Cable tie	
ETIM 7	EC000046 - Cable tie	
ETIM 8	EC000046 - Cable tie	
UNSPSC	39121703	
WEEE Category	Product Not in WEEE Scope	
IDEA Granular Category Code (IGCC)	5034 >> Cable ties	

Categories

Low Voltage Products and Systems \rightarrow Installation Products \rightarrow Wire Management and Connectivity \rightarrow Cable Ties

