

PRODUCT-DETAILS

TY5253MXR CBL TIE 50LB 11IN UV BLACK NYLON



EAN 541436 Catalog Description CBL TIE 50LB 11IN UV BLACK Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to 105 Degrees Cels F), Weather and Ultraviolet Resistant for Indoor and Outdoor Appli UL/EN/CSA62275 Type 2/21S Rated for AH-2 Plenum and as a Flexible Cable and Support, Length of 295mm (11.61 Inches), Width of 4.82mm (0.19 Inches), Thicl 1.3mm (0.05 Inches), Tensile Strength Rating of 222 Newtons (50 Pounds), Pr Ordering E-Number (Finland) EAN 541436 UPC 78621 Country of Origin Hung	ре	TY5253M
Catalog Description CBL TIE 50LB 11IN UV BLACK Catalog Description Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to 105 Degrees Cels F), Weather and Ultraviolet Resistant for Indoor and Outdoor Appli UL/EN/CSA62275 Type 2/21S Rated for AH-2 Plenum and as a Flexible Cable and Support, Length of 295mm (11.61 Inches), Width of 4.82mm (0.19 Inches), Thicl 1.3mm (0.05 Inches), Tensile Strength Rating of 222 Newtons (50 Pounds), Participant (Finland) E-Number (Finland) EAN 541436 UPC 78621 78621 Country of Origin Hung Selling Unit of Measure		7TCG009200R00
Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to 105 Degrees Cels F), Weather and Ultraviolet Resistant for Indoor and Outdoor Appli UL/EN/CSA62275 Type 2/21S Rated for AH-2 Plenum and as a Flexible Cable and Support, Length of 295mm (11.61 Inches), Width of 4.82mm (0.19 Inches), Thici 1.3mm (0.05 Inches), Tensile Strength Rating of 222 Newtons (50 Pounds), Cordering E-Number (Finland) EAN 541436 UPC 78621 Country of Origin 541436 Selling Unit of Measure		54143630656
F), Weather and Ultraviolet Resistant for Indoor and Outdoor Appli UL/EN/CSA62275 Type 2/21S Rated for AH-2 Plenum and as a Flexible Cable and Support, Length of 295mm (11.61 Inches), Width of 4.82mm (0.19 Inches), Thick 1.3mm (0.05 Inches), Tensile Strength Rating of 222 Newtons (50 Pounds), Participation (1.1000) E-Number (Finland) EAN 541436 UPC 78621 Country of Origin 78621 Country of Origin Hung Selling Unit of Measure		CBL TIE 50LB 11IN UV BLACK NYL
E-Number (Finland) EAN 541436 UPC 78621 Country of Origin Hung Selling Unit of Measure	UL/EN/CSA6 Support,	F), Weather and Ultraviolet Resistant for Indoor and Outdoor Application 2275 Type 2/21S Rated for AH-2 Plenum and as a Flexible Cable and Cond ength of 295mm (11.61 Inches), Width of 4.82mm (0.19 Inches), Thickness
EAN 541436 UPC 78621 Country of Origin Hung Selling Unit of Measure		
UPC 78621 Country of Origin Hung Selling Unit of Measure		
Country of Origin Hung Selling Unit of Measure		13700
Selling Unit of Measure		13700 54143630656
Dimensions		54143630656
Dimensions	re	54143630656 7862103930
	re	54143630656 7862103930 Hungary (F
Product Net Width	Ire	54143630656 7862103930 Hungary (F

© 2024 ABB. All rights reserved.

2024/04/03

Subject to change without notice

Product Net Depth /	11.6 in
Length	295 mm

Container Information	
Package Level 1 Units	100 piece
Package Level 2 Units	5000 piece
Package Level 2 Width	5.5 in 140 mm
Package Level 2 Height	5.5 in 140 mm
Package Level 2 Depth / Length	15.25 in 387 mm

Technical UL/CSA	
Flammability According to UL94	V-2

Brand / Label	Ty-Rap
Bundle Diameter	0.12 to 3.07 in 3 to 78 mm
Color	Black
Effective Date	19980621
Lock Type	Stainless Steel Barb
Material	Nylon/Polyamide 6.6
Product Name	NYLON CABLE TIES AND ACCESSORIES
Product Type	High Performance
RoHS Date	9AKK107991A8361
Special Functions	Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time.
Tensile Strength	50 lb 222 N
Thickness	0.05 in 1.3 mm

Certificates and Declarations	
Data Sheet, Technical Information	TDS000518
Declaration of Conformity - CE	9AKK107492A9841

Classifications	
ETIM 6	EC000046 - Cable tie
ETIM 7	EC000046 - Cable tie
ETIM 8	EC000046 - Cable tie
UNSPSC	39121703
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5034 >> Cable ties

Categories

Low Voltage Products and Systems \rightarrow Installation Products \rightarrow Wire Management and Connectivity \rightarrow Cable Ties

