

PRODUCT-DETAILS

## TY528MR CABLE TIE 50LB 14IN NATURAL NYLON

General Information			
Extended Product Type	TY528MR		
Product ID	7TCG009450R0183		
EAN	5414363065906		
Catalog Description	CABLE TIE 50LB 14IN NATURAL NYLON		
Long Description	Cable Tie, Natural Polyamide (Nylon 6.6) for Temperatures up to 85 Degrees Celsius (185 F) for Indoor Applications, UL/EN/CSA62275 Type 2/21S Rated for AH-2 Plenum or as a Flexible Cable and Conduit Support, Length of 360.5mm (14.2 Inches), Width of 4.82mm (0.19 Inches), Thickness of 1.4mm (0.05 Inches), Tensile Strength Rating of 222 Newtons (50 Pounds), Euroslot Packaging		
Ordering			
E-Number (Finland)	1381533		
EAN	5414363065906		
UPC	786210626253		
Country of Origin	Hungary (HU)		
Selling Unit of Measure	<u>each</u>		
<u>Dimensions</u>			
Product Net Width	0.189 in 4.82 mm		
Product Net Depth /	14.2 in		

TY528MR 2

361 mm Length **Container Information** Package Level 1 Units 100 piece Package Level 2 Units 5000 piece Package Level 2 Width 10.2 in 259 mm Package Level 2 Height 13.8 in 351 mm Package Level 2 Depth / 19.7 in 500 mm Length Technical UL/CSA V-2 Flammability According to UL94 Additional Information Brand / Label Ty-Rap 0.12 to 4.02 in **Bundle Diameter** 3 to 102 mm Color Natural Effective Date 19980621 Lock Type Stainless Steel Barb Nylon/Polyamide 6.6 Material TYRAP PK 100 PCS NATURAL Product Name Product Type High Performance RoHS Date 9AKK107991A8366 Special Functions Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time. Tensile Strength 222 N Thickness 0.05 in 1.3 mm Certificates and Declarations Data Sheet, Technical TDS000518 Information 9AKK107492A9841 **Declaration of Conformity** Classifications ETIM 6 EC000046 - Cable tie ETIM 7 EC000046 - Cable tie EC000046 - Cable tie ETIM 8 UNSPSC 39121703

WEEE Category
IDEA Granular Category

Code (IGCC)

Product Not in WEEE Scope

5034 >> Cable ties

TY528MR 3

Ca		

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Installation\ Products \rightarrow Wire\ Management\ and\ Connectivity \rightarrow Cable\ Ties$