

PRODUCT-DETAILS

TY200-18X-C

80N UV CABLE TIE 200MM DIS



General Information

| | |
|-----------------------|--|
| Extended Product Type | TY200-18X-C |
| Product ID | 7TCG054360R0434 |
| EAN | 5415022524369 |
| Catalog Description | 80N UV CABLE TIE 200MM DIS |
| Long Description | "Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to 115 Degrees Celsius, Weather and Ultraviolet Resistant for Indoor and Outdoor Applications, UL/IEC 62275 Type 2/21S Rated for AH-2 Plenum and as a Flexible Cable and Conduit Support, Length of 200mm, Width of 2.5mm, Thickness of 1.1mm , Tensile Strength Rating of 80 Newtons, 100 Pack" |

Ordering

| | |
|-------------------------|---------------|
| EAN | 5415022524369 |
| UPC | 786210362335 |
| Country of Origin | China (CN) |
| Selling Unit of Measure | each |

Container Information

| | |
|------------------------|------------------|
| Package Level 1 Units | 100 piece |
| Package Level 1 Width | 3.74 in 95 mm |
| Package Level 1 Height | 0.59 in |

| | |
|--------------------------------|--------------------|
| | 15 mm |
| Package Level 1 Depth / Length | 12.2 in 310 mm |
| Package Level 2 Units | 10000 piece |
| Package Level 2 Width | 15.75 in 400 mm |
| Package Level 2 Height | 4.72 in 120 mm |
| Package Level 2 Depth / Length | 19.69 in 500 mm |

Additional Information

| | |
|-------------------|--|
| Brand / Label | Ty-Fast |
| Bundle Diameter | 52.5 mm 2.067 in |
| Color | Black |
| Effective Date | 20220125 |
| Lock Type | Plastic Pawl |
| Product Main Type | CABLE TIES AND ACCESSORIES |
| Product Name | PLASTIC CABLE TIE |
| Product Type | General Purpose |
| Special Functions | "The integrally formed polyamide pawl combines low insertion and high locking strength. The low profile head significantly reduces the potential for snagging during installation. Quick and easy pull through increases productivity, reduces operator fatigue. Tail with finger grip design that helps operator grasp and pull ties snugly. Sure grip tab keeps the tail from popping out while being treated, then holds it it securely for final tightening by hand or tool" |
| Standards | UL E49405 |
| Tensile Strength | 80 N 18 lb |
| Thickness | 1.1 mm 0.043 in |

Certificates and Declarations

| | |
|-----------------------------------|-----------|
| Data Sheet, Technical Information | TDS000751 |
|-----------------------------------|-----------|

Classifications

| | |
|------------------------------------|----------------------|
| ETIM 6 | EC000046 - Cable tie |
| ETIM 7 | EC000046 - Cable tie |
| ETIM 8 | EC000046 - Cable tie |
| UNSPSC | 39121703 |
| IDEA Granular Category Code (IGCC) | 5034 >> Cable ties |

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Cable Ties

