


**COAXIAL CONNECTOR, 7/16, 50 Ohm, Right angle cable plug (male)**

16\_716-50-5-2/003\_-

**Properties**

- Rugged connection for COM-Applications
- For medium and high power connection
- Applicable in frequencies up to 7.5 GHz
- IEC Standardized



Product configuration		
Interface type	Gender	Standard
7/16	plug	IEC 61169-4_CECC 22190_DIN 47223_VG 95250

Interface and material data		
Piece parts	Material	Plating
Centre contact	Brass	Silver Plating
Outer conductor	Brass	Silver Plating
Body	Brass	Silver Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	

Electrical data	
Impedance	50 $\Omega$
Interface frequency	7.5 GHz

Electrical Data (frequency related)		
Frequency range	Return loss	VSWR
0 GHz ... 2.5 GHz	32 dB	1.05

Mechanical data	
Weight	0.15 kg
Mating cycles	500
Cable entry centre contact	soldered
Cable entry outer contact	clamped

**COAXIAL CONNECTOR, 7/16, 50 Ohm, Right angle cable plug (male)**

16\_716-50-5-2/003\_-

Environmental data	
Operation temperature	-65 °C ... 165°C

Ordering Information Table		
Item number	Item description	Packaging type
23016774	16_716-50-5-2/003_-Z	Bulk 10 pcs

Suitable cables	
Cable group	M5 - 5 mm / 50 Ohm
Suitable cables	SUCOFEEED_1/4_HF
	SUCOFEEED_1/4_HF_FR
Additional cables	FSJ1-50

Additional Information	
Only as assembly	No

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.  
DOCUMENT PIM-P3171 / Date of publication: 25.11.2023 / uncontrolled copy