

COAXIAL CONNECTOR, C, 50 Ohm, Right angle cable plug (male)

16_C-50-3-3/133_N

Properties

- Easy coupling and decoupling
- Applicable in frequencies up to 11 GHz



Product configuration		
Interface type	Gender	Standard
C	plug	IEC 60169-7_MIL-STD-348A/302
Interface and material data		
Piece parts	Material	Plating
Centre contact	Copper Beryllium / Brass	SUCOPRO / Gold Plating
Outer conductor	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	
Electrical data		
Impedance	50 Ω	
Interface frequency	11 GHz	
Mechanical data		
Weight	0.0551 kg	
Mating cycles	500	
Cable entry centre contact	soldered	
Cable entry outer contact	clamped	
Environmental data		
Operation temperature	-65 °C ... 165°C	

COAXIAL CONNECTOR, C, 50 Ohm, Right angle cable plug (male)

16_C-50-3-3/133_N

Ordering Information Table		
Item number	Item description	Packaging type
22642051	16_C-50-3-3/133_NE	Single

Suitable cables	
Cable group	U9 - 3 mm / 50 Ohm
Suitable cables	RG_142_B/U
	RG_223_/U

Additional Information	
Only as assembly	No

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P3144 / Date of publication: 25.11.2023 / uncontrolled copy