

COAXIAL CONNECTOR, C, 50 Ohm, Right angle cable plug (male)

16_C-50-4-4/122_N

Properties

- Suitable for use with KX_EN4604-010 cable
- Applicable in frequencies up to 6 GHz
- Compliant with EN4652-411-B50 interface standard



Product configuration		
Interface type	Gender	Standard
C	plug	EN4652-411-B50

Interface and material data		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer conductor	Brass	Nickel Plating
Body	Brass	Nickel Plating
Other body part	Stainless Steel	Passivated (Plating)
Insulator	PTFE (Polytetrafluoroethylene)	
Coupling nut	Brass	Nickel Plating
Gasket	VMQ (Silicone rubber)	

Electrical data	
Impedance	50 Ω
Interface frequency	6 GHz

Electrical Data (frequency related)		
Frequency range	Return loss	VSWR
0 GHz ... 6 GHz	17.7 dB	1.3

Mechanical data	
Weight	0.045 kg
Mating cycles	500
Cable entry centre contact	plugged
Cable entry outer contact	clamped

COAXIAL CONNECTOR, C, 50 Ohm, Right angle cable plug (male)

16_C-50-4-4/122_N

Environmental data	
Operation temperature	-60 °C ... 165 °C
Ingress protection (IP Rating)	Mated / IP67

Ordering Information Table		
Item number	Item description	Packaging type
84114106	16_C-50-4-4/122_NE	Single

Suitable cables	
Cable group	U91 - KX_EN4604-010
Suitable cables	KX_EN4604-010

Additional Information	
Only as assembly	No

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P3143 / Date of publication: 17.07.2024 / uncontrolled copy