


**COAXIAL CONNECTOR, MCX, 50 Ohm, Right angle cable plug (male)**

16\_MCX-50-1-7/133\_N

**Properties**

- Small size
- Easy to connect and disconnect
- Wide range of board connectors and cable connectors available



Product configuration		
Interface type	Gender	Standard
MCX	plug	IEC 60169-36_CECC 22220
Interface and material data		
Piece parts	Material	Plating
Centre contact	Brass	Gold Plating (Nickel underplated)
Outer conductor	Copper Beryllium Alloy	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Crimp ferrule	Copper	SUCOPLATE (R) Plating
Electrical data		
Impedance	50 Ω	
Interface frequency	6 GHz	
Mechanical data		
Weight	0.0008 kg	
Mating cycles	500	
Cable entry centre contact	soldered	
Cable entry outer contact	crimped	
Environmental data		
Operation temperature	-55 °C ... 155°C	

**COAXIAL CONNECTOR, MCX, 50 Ohm, Right angle cable plug (male)**

16\_MCX-50-1-7/133\_N

<b>Ordering Information Table</b>		
Item number	Item description	Packaging type
22658308	16_MCX-50-1-7/133_NH	Bulk 100 pcs

<b>Suitable cables</b>	
Cable group	U1 - 1 mm / 50 Ohm
Suitable cables	ENVIROFLEX_178
	RG_178_B/U
	RG_196_A/U

<b>Additional Information</b>	
Only as assembly	No

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.  
DOCUMENT PIM-P3135 / Date of publication: 25.11.2023 / uncontrolled copy