

COAXIAL CONNECTOR, MMBX, 50 Ohm, Right angle cable plug (male)

16_MMBX-50-2-1/111_N

Properties

- Smallest board-to-board distance
- Very high frequencies
- Excellent return loss values
- Blind mateable
- Reliable and secure connection



Product configuration		
Interface type	Gender	Standard
MMBX	plug	HUBER+SUHNER-MMBX

Interface and material data		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer conductor	Copper Beryllium Alloy	SUCOPRO Plating
Body	Brass	SUCOPRO Plating
Insulator	PFA / PTFE	
Crimp ferrule	Copper	Gold Plating (without Nickel underplating)

Electrical data	
Impedance	50 Ω
Interface frequency	12.4 GHz

Mechanical data	
Weight	0.0011 kg
Mating cycles	100
Cable entry centre contact	soldered
Cable entry outer contact	crimped

Environmental data	
Operation temperature	-55 °C ... 155°C

COAXIAL CONNECTOR, MMBX, 50 Ohm, Right angle cable plug (male)

16_MMBX-50-2-1/111_N

Ordering Information Table		
Item number	Item description	Packaging type
23001747	16_MMBX-50-2-1/111_NE	Single

Suitable cables	
Cable group	U2 - 2 mm / 50 Ohm
Suitable cables	RG_174_/U
	RG_188_A/U
	RG_316_/U

Additional Information	
Only as assembly	No

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P3121 / Date of publication: 25.11.2023 / uncontrolled copy