


COAXIAL CONNECTOR, N, 50 Ohm, Right angle cable plug (male)

16_N-50-3-103/133_N

Properties

- Screwed coupling mechanism for sturdy and reliable connection
- IP rating (interface, mated) IP67
- Interface dimensions according IEC/MIL



Product configuration		
Interface type	Gender	Standard
N	plug	IEC 61169-16_MIL-STD-348A/304_CECC 22210
Interface and material data		
Piece parts	Material	Plating
Centre contact	Brass	Gold Plating (Nickel underplated)
Outer conductor	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	
Electrical data		
Impedance	50 Ω	
Interface frequency	11 GHz	
Mechanical data		
Weight	0.0381 kg	
Mating cycles	500	
Cable entry centre contact	soldered	
Cable entry outer contact	clamped	
Environmental data		
Operation temperature	-65 °C ... 165°C	

COAXIAL CONNECTOR, N, 50 Ohm, Right angle cable plug (male)

16_N-50-3-103/133_N

Ordering Information Table		
Item number	Item description	Packaging type
22651610	16_N-50-3-103/133_NE	Single

Suitable cables	
Cable group	X25 - 3 mm / 50 Ohm
	U9 - 3 mm / 50 Ohm
	U7 - 3 mm / 50 Ohm
	U11 - 3 mm / 50 Ohm
Suitable cables	RG_58_C/U
	RG_223_/U
	G_03233_D
Additional cables	ENVIROFLEX_400

Additional Information	
Only as assembly	No

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P3098 / Date of publication: 25.11.2023 / uncontrolled copy