

COAXIAL CONNECTOR, QMA, 50 Ohm, Right angle cable plug (male)

16_QMA-50-3-1/133_N

Properties

- Excellent electrical performance
- High packing density
- Applicable in frequencies up to 18 GHz
- Easy to mate - No torque or tooling required
- Return loss optimized DC to 6 GHz



Product configuration		
Interface type	Gender	Standard
QMA	plug	QMA QLF compliant
Interface and material data		
Piece parts	Material	Plating
Centre contact	Brass	SUCOPRO Plating
Outer conductor	Bronze	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Crimp ferrule	Copper	SUCOPLATE (R) Plating
Electrical data		
Impedance	50 Ω	
Interface frequency	18 GHz	
Mechanical data		
Weight	0.0081 kg	
Mating cycles	100	
Cable entry centre contact	soldered	
Cable entry outer contact	crimped	
Environmental data		
Operation temperature	-40 °C ... 85°C	

COAXIAL CONNECTOR, QMA, 50 Ohm, Right angle cable plug (male)

16_QMA-50-3-1/133_N

Ordering Information Table		
Item number	Item description	Packaging type
23017686	16_QMA-50-3-1/133_NE	Single
23017687	16_QMA-50-3-1/133_NH	Bulk 100 pcs

Suitable cables	
Cable group	U9 - 3 mm / 50 Ohm
	U41 - 3 mm / 50 Ohm
	U11 - 3 mm / 50 Ohm
Suitable cables	ENVIROFLEX_400
	RADOX_RF_400
	RG_223_/U
	RG_400_/U
Additional cables	ENVIROFLEX_142
	RADOX_RF_142

Additional Information	
Only as assembly	No

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P3060 / Date of publication: 25.11.2023 / uncontrolled copy