

**COAXIAL CONNECTOR, QN, 50 Ohm, Right angle cable plug (male)**

16\_QN-50-2-1/133\_N

**Properties**

- Same performance but smaller than N-Interface
- High packing density
- Applicable in frequencies up to 11 GHz
- Easy to mate - No torque or tooling required



Product configuration		
Interface type	Gender	Standard
QN	plug	QN QLF compliant

  

Interface and material data		
Piece parts	Material	Plating
Centre contact	Brass	SUCOPRO Plating
Outer conductor	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	EPDM (Ethylene propylene diene rubber)	
Crimp ferrule	Copper	SUCOPLATE (R) Plating

  

Electrical data	
Impedance	50 Ω
Interface frequency	11 GHz

  

Electrical Data (frequency related)		
Frequency range	Return loss	VSWR
0 GHz ... 1 GHz	20 dB	1.22

  

Mechanical data	
Mating cycles	100
Cable entry centre contact	soldered
Cable entry outer contact	crimped

**COAXIAL CONNECTOR, QN, 50 Ohm, Right angle cable plug (male)**

16\_QN-50-2-1/133\_N

Environmental data	
Operation temperature	-40 °C ... 125°C

Ordering Information Table		
Item number	Item description	Packaging type
84022911	16_QN-50-2-1/133_NE	Single

Suitable cables	
Cable group	U4 - 2 mm / 50 Ohm
Suitable cables	G_02232_D ENVIROFLEX_316_D

Additional Information	
Only as assembly	No

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.  
DOCUMENT PIM-P3054 / Date of publication: 25.11.2023 / uncontrolled copy