


**COAXIAL CONNECTOR, TNC, 50 Ohm, Right angle cable plug (male)**

16\_TNC-50-3-18/133\_N

**Properties**

- Threaded coupling mechanism improves control over the interface dimensions
- Used under a higher environmental load than BNC
- Available for 50 ohm and 75 ohm applications
- Applicable in frequencies up to 11 GHz

**Product configuration**

Interface type	Gender	Standard
TNC	plug	IEC 60169-17_MIL-STD-348A/313_CECC 22200

**Interface and material data**

Piece parts	Material	Plating
Centre contact	Bronze / Brass	Gold Plating (Nickel underplated)
Outer conductor	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	
Crimp ferrule	Copper	SUCOPLATE (R) Plating

**Electrical data**

Impedance	50 $\Omega$
Interface frequency	11 GHz

**Mechanical data**

Weight	0.0293 kg
Mating cycles	500
Cable entry centre contact	crimped
Cable entry outer contact	crimped

**Environmental data**

Operation temperature	-65 °C ... 165 °C
-----------------------	-------------------

**COAXIAL CONNECTOR, TNC, 50 Ohm, Right angle cable plug (male)**

16\_TNC-50-3-18/133\_N

Ordering Information Table		
Item number	Item description	Packaging type
22543606	16_TNC-50-3-18/133_NE	Single

Suitable cables	
Cable group	U9 - 3 mm / 50 Ohm
Suitable cables	RG_142_B/U
	RG_223_U
Additional cables	RADOX_RF_142

Additional Information	
Only as assembly	No

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.  
DOCUMENT PIM-P2979 / Date of publication: 25.11.2023 / uncontrolled copy