

**COAXIAL CONNECTOR, UHF, X Ohm, Right angle cable plug (male)**

16\_UHF-0-3-4/023\_

**Properties**

- Mateable with 4 mm banana plugs
- Applicable in frequencies up to 200 MHz



Product configuration		
Interface type	Gender	Standard
UHF	plug	IEC 60169-12
Interface and material data		
Piece parts	Material	Plating
Centre contact	Brass	Silver Plating
Outer conductor	Brass	Nickel Plating
Body	Brass	Nickel Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	Nickel Plating
Crimp ferrule	Copper	SUCOPLATE (R) Plating
Electrical data		
Interface frequency	0.2 GHz	
Mechanical data		
Weight	0.0319 kg	
Mating cycles	500	
Cable entry centre contact	soldered	
Cable entry outer contact	crimped	
Environmental data		
Operation temperature	-55 °C ... 165°C	

**COAXIAL CONNECTOR, UHF, X Ohm, Right angle cable plug (male)**

16\_UHF-0-3-4/023\_

Ordering Information Table		
Item number	Item description	Packaging type
22542757	16_UHF-0-3-4/023_-E	Single

  

Suitable cables	
Cable group	U7 - 3 mm / 50 Ohm
Suitable cables	GX_03272
	G_03232
	RG_58_C/U

  

Additional Information	
Only as assembly	No

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.  
DOCUMENT PIM-P2957 / Date of publication: 25.11.2023 / uncontrolled copy