

**COAXIAL CONNECTOR, N, 50 Ohm, Straight cable jack (female)**

21\_N-50-9-9/033\_-

**Properties**

- Field mountable connector series Quick-fit
- Screwed coupling mechanism for sturdy and reliable connection
- IP rating (interface, mated) IP67
- Interface dimensions according IEC/MIL



Product configuration		
Interface type	Gender	Standard
N	jack	IEC 61169-16_MIL-STD-348A/304_CECC 22210

Interface and material data		
Piece parts	Material	Plating
Centre contact	Bronze	Silver Plating
Outer conductor	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	NR (Natural Rubber)	

Electrical data	
Impedance	50 $\Omega$
Interface frequency	11 GHz

Electrical Data (frequency related)		
Frequency range	Return loss	VSWR
0 GHz ... 3 GHz	30 dB	1.065

Mechanical data	
Weight	0.1121 kg
Mating cycles	500
Cable entry centre contact	plugged
Cable entry outer contact	clamped

**COAXIAL CONNECTOR, N, 50 Ohm, Straight cable jack (female)**

21\_N-50-9-9/033\_-

Environmental data	
Operation temperature	-40 °C ... 85 °C

Ordering Information Table		
Item number	Item description	Packaging type
22660312	21_N-50-9-9/033_-E	Single

Suitable cables	
Cable group	M9 - 9 mm / 50 Ohm
Suitable cables	SUCOFEED_1/2_HF_FR
	SUCOFEED_1/2_HF

Additional Information	
Remarks	Stripping tool: 23001006 74_Z-0-9-12
Only as assembly	No

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.  
DOCUMENT PIM-P2874 / Date of publication: 03.09.2024 / uncontrolled copy