


**COAXIAL CONNECTOR, SK, 50 Ohm, Straight cable jack (female)**

21\_SK-50-2-61/199\_N

**Properties**

- The shortened male pin ensures a non-destructive mating process
- Particularly well suited for semi-rigid, semi-flex and flexible cable
- Mechanical intermateable with SMA and PC 3.5 (3.5 mm standard)



Product configuration		
Interface type	Gender	Standard
SK	jack	MIL-STD-348A/323
Interface and material data		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer conductor	Stainless Steel	Passivated (Plating)
Body	Stainless Steel	Passivated (Plating)
Insulator	PPE (Polyphenylene ether, PPO)	
Electrical data		
Impedance	50 Ω	
Interface frequency	40 GHz	
Electrical Data (frequency related)		
Frequency range	Return loss	VSWR
0 GHz ... 40 GHz	21 dB	1.2
Mechanical data		
Weight	0.00426 kg	
Mating cycles	500	
Cable entry centre contact	plugged	
Cable entry outer contact	soldered	
Environmental data		
Operation temperature	-55 °C ... 125°C	

**COAXIAL CONNECTOR, SK, 50 Ohm, Straight cable jack (female)**

21\_SK-50-2-61/199\_N

Ordering Information Table		
Item number	Item description	Packaging type
84094378	21_SK-50-2-61/199_NE	Single

Suitable cables	
Cable group	Y11 - 2 mm / 50 Ohm
Suitable cables	MULTIFLEX_86

Additional Information	
Only as assembly	No

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.  
DOCUMENT PIM-P2860 / Date of publication: 25.11.2023 / uncontrolled copy