

COAXIAL CONNECTOR, N, 50 Ohm, Straight cable jack (female)

21_N-50-10-1/133_U

Properties

- Screwed coupling mechanism for sturdy and reliable connection
- IP rating (interface, mated) IP67
- Interface dimensions according IEC/MIL

**Product configuration**

Gender	Standard
jack	IEC 61169-16_MIL-STD-348A/304_CECC 22210

Interface and material data

Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Outer conductor	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Crimp ferrule	Brass	SUCOPLATE (R) Plating

Electrical data

Impedance	50 Ω
Interface frequency	11 GHz

Mechanical data

Weight	0.0381 kg
Mating cycles	500
Cable entry centre contact	plugged
Cable entry outer contact	crimped

Environmental data

Operation temperature	-65 °C ... 165°C
-----------------------	------------------

COAXIAL CONNECTOR, N, 50 Ohm, Straight cable jack (female)

21_N-50-10-1/133_U

Ordering Information Table		
Item number	Item description	Packaging type
23003072	21_N-50-10-1/133_UF	Bulk 50 pcs
Suitable cables		
Cable group	S39 - 10 mm / 50 Ohm	
Suitable cables	S_10172_B-11	
	S_10162_B-11	
Additional Information		
Only as assembly	No	

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P2900 / Date of publication: 25.11.2023 / uncontrolled copy