

**COAXIAL CONNECTOR, N, 50 Ohm, Straight cable jack (female)**

21\_N-50-23-10/003\_-

**Properties**

- Field mountable connector series Quick-fit
- Screwed coupling mechanism for sturdy and reliable connection
- IP rating (interface, mated) IP67
- Interface dimensions according IEC/MIL



Product configuration	
Gender	Standard
jack	IEC 61169-16_MIL-STD-348A/304_CECC 22210

Interface and material data		
Piece parts	Material	Plating
Centre contact	Bronze	Silver Plating
Outer conductor	Brass	Silver Plating
Body	Brass	Silver / SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	NR (Natural Rubber)	

Electrical data	
Impedance	50 Ω
Interface frequency	11 GHz

Electrical Data (frequency related)		
Frequency range	Return loss	VSWR
0 GHz ... 2.5 GHz	30 dB	1.065

Mechanical data	
Weight	0.3071 kg
Mating cycles	500
Cable entry centre contact	plugged
Cable entry outer contact	clamped

**COAXIAL CONNECTOR, N, 50 Ohm, Straight cable jack (female)**

21\_N-50-23-10/003\_-

Environmental data		
Operation temperature	-40 °C ... 85 °C	
Ordering Information Table		
Item number	Item description	Packaging type
23000307	21_N-50-23-10/003_-E	Single
Suitable cables		
Cable group	M23 - 22 mm / 50 Ohm	
Suitable cables	SUCOFEED_7/8_FR	
	SUCOFEED_7/8	
Additional Information		
Remarks	Stripping tools: 85002265 74_Z-0-23-21 for 7/8" & 7/8"HF 84147229 74_Z-0-23-22 for 7/8" LA	
Only as assembly	No	

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/ EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.  
DOCUMENT PIM-P2893 / Date of publication: 03.09.2024 / uncontrolled copy