

# COAXIAL CONNECTOR, BNO, X Ohm, Straight bulkhead cable jack (female)

24\_BNO-0-4-1/133\_N

## Properties

- Used with balanced twin-conductor cables with 75 ohm to 130 ohm impedance
- Suitable for applications up to 200 MHz
- Ideal for computer networks and process control



## Product configuration

Gender	Standard
jack	IEC 60169-22

## Interface and material data

Piece parts	Material	Plating
Centre contact	Copper Beryllium / Brass	Gold Plating (Nickel underplated)
Outer conductor	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	ETFE (Ethylene tetrafluoroethylene)	
Gasket	VMQ (Silicone rubber)	
Fastening nut	Brass	SUCOPLATE (R) Plating
Washer	Bronze	SUCOPLATE (R) Plating
Crimp ferrule	Copper	SUCOPLATE (R) Plating

## Electrical data

Interface frequency	0.2 GHz
---------------------	---------

## Mechanical data

Weight	0.0202 kg
Mating cycles	500
Cable entry centre contact	soldered
Cable entry outer contact	crimped

## Environmental data

Operation temperature	-50 °C ... 125°C
-----------------------	------------------

## Ordering Information Table

Item number	Item description	Packaging type
22541086	24_BNO-0-4-1/133_NE	Single

**COAXIAL CONNECTOR, BNO, X Ohm, Straight bulkhead cable jack (female)**

24\_BNO-0-4-1/133\_N

<b>Suitable cables</b>	
Cable group	V1 - 2 mm / 78 Ohm
Suitable cables	RG_108_A/U
Additional cables	K_05790

  

<b>Additional Information</b>	
Only as assembly	No

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.  
DOCUMENT PIM-P2649 / Date of publication: 25.11.2023 / uncontrolled copy