


COAXIAL CONNECTOR, BNC, 75 Ohm, Straight panel cable jack (female), flange mount

25_BNC-75-2-8/133_N

Properties

- Useful for frequently coupled and uncoupled connections
- Available for 50 ohm and 75 ohm applications
- Applicable in frequencies up to 4 GHz



Product configuration

Gender	Standard
jack	Interface compatible with IEC 61169-8

Interface and material data

Piece parts	Material	Plating
Centre contact	Copper Beryllium / Brass	Gold Plating (Nickel underplated)
Outer conductor	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Crimp ferrule	Copper	SUCOPLATE (R) Plating

Electrical data

Impedance	75 Ω
Interface frequency	1 GHz

Mechanical data

Weight	0.0168 kg
Mating cycles	500
Cable entry centre contact	crimped
Cable entry outer contact	crimped

Environmental data

Operation temperature	-65 °C ... 165°C
-----------------------	------------------

COAXIAL CONNECTOR, BNC, 75 Ohm, Straight panel cable jack (female), flange mount

25_BNC-75-2-8/133_N

Ordering Information Table		
Item number	Item description	Packaging type
22641791	25_BNC-75-2-8/133_NE	Single
Suitable cables		
Cable group	U5 - 2 mm / 75 Ohm	
Suitable cables	ENVIROFLEX_179	
	RG_179_B/U	
	RG_187_A/U	
Additional Information		
Only as assembly	No	

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/ EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P2498 / Date of publication: 25.11.2023 / uncontrolled copy