

COAXIAL CONNECTOR, C, 50 Ohm, Straight panel cable jack (female), flange mount

25_C-50-6-1/122_N

Properties

- Suitable for use with KW_EN4604-009 cable
- Compliant with EN4652-412-A50 interface standard
- Compliant with EN4652-412-A50 interface standard



Product configuration

Interface type	Gender	Standard
C	jack	EN4652-412-A50

Interface and material data

Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer conductor	Brass	Nickel Plating
Body	Brass	Nickel Plating
Other body part	Stainless Steel	Passivated (Plating)
Insulator	PTFE (Polytetrafluoroethylene)	
Gasket	VMQ (Silicone rubber)	

Electrical data

Impedance	50 Ω
Interface frequency	6 GHz

Electrical Data (frequency related)

Frequency range	Return loss	VSWR
0 GHz ... 6 GHz	23.1 dB	1.15

Mechanical data

Weight	0.047 kg
Mating cycles	500
Cable entry centre contact	plugged
Cable entry outer contact	clamped

COAXIAL CONNECTOR, C, 50 Ohm, Straight panel cable jack (female), flange mount
25_C-50-6-1/122_N

Environmental data		
Operation temperature		-60 °C ... 165 °C
Ordering Information Table		
Item number	Item description	Packaging type
85003551	25_C-50-6-1/122_NE	Single
Suitable cables		
Cable group		U90 - KW - EN4604-009
Additional cables		KW_EN4604-009
Additional Information		
Only as assembly		No

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/ EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P2495 / Date of publication: 13.11.2024 / uncontrolled copy