

COAXIAL TERMINATION, 50 Ohm, N-precision, jack (female)

6500_N-50-2/133_N

Properties

- Various bandwidth
- Impedance matched
- Standard or precision types
- Low and medium power



Product configuration		
Interface	Gender	Standard
N-precision	jack (female)	IEC 60169-16_MIL-STD-348A/304_CECC 22210

Electrical data	
Impedance	50Ω
Operating frequency	0 GHz ... 18 GHz
VSWR	1.3
Return loss	17.7 dB

Electrical Data (power)	
Average power	2 W at 25 °C ambient temperature. Linearly derated to 1.2 W at 65 °C ambient temperature.
Peak power	500 W peak power

Interface and material data		
Interface	N-precision / jack (female)	
Piece parts	Material	Plating
Centre contact	Bronze	Gold Plating
Outer conductor	Brass	Tri-metal Plating
Body	Brass	Tri-metal Plating
Insulator	PTFE (Polytetrafluoroethylene)	
Piece parts	Material	Plating

Mechanical data	
Weight	0.03 kg

COAXIAL TERMINATION, 50 Ohm, N-precision, jack (female)

6500_N-50-2/133_N

Environmental data	
Operation temperature	-30 °C ... 65 °C

Ordering Information Table	
Item number	Item description
85218435	6500_N-50-2/133_N

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.

DOCUMENT PIM-P1739 / Date of publication: 28.11.2023 / uncontrolled copy