

COAXIAL TERMINATION, 50 Ohm, N, plug (male)

65025_N-50-1/133_N

Properties

- Various bandwidth
- Impedance matched
- Standard or precision types
- Low and medium power



Product configuration		
Interface	Gender	Standard
N	plug (male)	IEC 60169-16_MIL-STD-348A/304_CECC 22210

Electrical data	
Impedance	50Ω
Operating frequency	0 GHz ... 6 GHz
VSWR	1.25
Return loss	19.08 dB

Electrical Data (power)	
Average power	25 W at 25 °C ambient temperature. Linearly derated to 2.5 W at 100 °C ambient temperature.
Peak power	1000 W, 5 μs pulse width, 1 % duty cycle

Interface and material data		
Interface	N / plug (male)	
Piece parts	Material	Plating
Centre contact	Brass	Gold Plating
Outer conductor	Brass	Tri-metal Plating
Body	Aluminium	Anodized
Insulator	PTFE (Polytetrafluoroethylene)	
Coupling nut	Brass	Tri-metal Plating
Piece parts	Material	Plating

Mechanical data	
Weight	0.125 kg

COAXIAL TERMINATION, 50 Ohm, N, plug (male)

65025_N-50-1/133_N

Environmental data	
Operation temperature	-55 °C ... 100 °C

Ordering Information Table	
Item number	Item description
85218432	65025_N-50-1/133_NE

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.

DOCUMENT PIM-P1729 / Date of publication: 28.11.2023 / uncontrolled copy