

**COAXIAL TERMINATION, 50 Ohm, SMA, jack (female)**

6515.19.B

**Properties**

- Various bandwidth
- Impedance matched
- Standard or precision types
- Low and medium power



Product configuration		
Interface	Gender	Standard
SMA	jack (female)	IEC 60169-15_MIL-STD-348A/310_CECC 22110

Electrical data	
Impedance	50Ω
Operating frequency	0 GHz ... 12.4 GHz
VSWR	1.25
Return loss	19.1 dB

Electrical Data (frequency related)		
Frequency range	VSWR max	Return loss
0 GHz to 1 GHz	1.05	
1 GHz to 4 GHz	1.1	
4 GHz to 10 GHz	1.2	
10 GHz to 12.4 GHz	1.25	

Electrical Data (power)	
Average power	15 W at 25 °C ambient temperature. Linearly derated to W at 130 °C ambient temperature.
Peak power	1000 W, 5 μs pulse width, 0.05 % duty cycle

Interface and material data		
Interface	SMA / jack (female)	
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Outer conductor	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Body	Aluminium	Anodized

**COAXIAL TERMINATION, 50 Ohm, SMA, jack (female)**

6515.19.B

Interface and material data		
Insulator	PFA / PTFE	
Piece parts	Material	Plating
Mechanical data		
Weight	0.08 kg	
Environmental data		
Operation temperature	-40 °C ... 130°C	
Ordering Information Table		
Item number	Item description	
22544580	6515.19.B	

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.

DOCUMENT PIM-P1716 / Date of publication: 09.11.2023 / uncontrolled copy