

**COAXIAL TERMINATION, 50 Ohm, N, plug (male)**

6525.17.AA

**Properties**

- Various bandwidth
- Impedance matched
- Standard or precision types
- Low and medium power



Product configuration		
Interface	Gender	Standard
N	plug (male)	IEC 60169-16_MIL-STD-348A/304_CECC 22210

Electrical data	
Impedance	50Ω
Operating frequency	0 GHz ... 5 GHz
VSWR	1.2
Return loss	20.8 dB

Electrical Data (frequency related)		
Frequency range	VSWR max	Return loss
0 GHz to 2 GHz	1.1	26.4 dB
2 GHz to 5 GHz	1.2	20.8 dB

Electrical Data (power)	
Average power	25 W at 25 °C ambient temperature. Linearly derated to W at 150 °C ambient temperature.
Peak power	1500 W, 5 μs pulse width, 0.05 % duty cycle

Interface and material data		
Interface	N / plug (male)	
<b>Piece parts</b>	<b>Material</b>	<b>Plating</b>
Centre contact	Brass	Gold Plating (without Nickel underplating)
Outer conductor	Brass	SUCOPLATE (R) Plating
Body	Aluminium	Anodized
Insulator	PFA / PTFE	

**COAXIAL TERMINATION, 50 Ohm, N, plug (male)**

6525.17.AA

Interface and material data		
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	
Piece parts	Material	Plating

Mechanical data	
Weight	0.147 kg

Environmental data	
Operation temperature	-40 °C ... 150°C

Ordering Information Table	
Item number	Item description
22642248	6525.17.AA

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.

DOCUMENT PIM-P1715 / Date of publication: 09.11.2023 / uncontrolled copy