

**COAXIAL TERMINATION, 50 Ohm, BNC, jack (female)**

65\_BNC-50-0-35/133\_N

**Properties**

- Various bandwidth
- Impedance matched
- Standard or precision types
- Low and medium power

**Product configuration**

Interface	Gender	Standard
BNC	jack (female)	IEC 60169-8_MIL-STD-348A/301_CECC 22120

**Electrical data**

Impedance	50Ω
Operating frequency	0 GHz ... 2 GHz
VSWR	1.2
Return loss	20.8 dB

**Electrical Data (frequency related)**

Frequency range	VSWR max	Return loss
0 GHz to 1 GHz	1.05	
1 GHz to 1.5 GHz	1.1	
1.5 GHz to 2 GHz	1.2	

**Electrical Data (power)**

Average power	1 W at 30 °C ambient temperature. Linearly derated to W at 130 °C ambient temperature.
Peak power	2000 W peak power

**Interface and material data**

Interface	BNC / jack (female)	
<b>Piece parts</b>	<b>Material</b>	<b>Plating</b>
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer conductor	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	

**COAXIAL TERMINATION, 50 Ohm, BNC, jack (female)**

65\_BNC-50-0-35/133\_N

Interface and material data		
Piece parts	Material	Plating
Mechanical data		
Weight	0.016 kg	
Environmental data		
Operation temperature	-40 °C ... 130°C	
Ordering Information Table		
Item number	Item description	
22648680	65_BNC-50-0-35/133_NE	

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.

DOCUMENT PIM-P1780 / Date of publication: 09.11.2023 / uncontrolled copy