

COAXIAL TERMINATION, 50 Ohm, MMCX, plug (male)

65_MMCX-50-0-2/111_N

Properties

- Various bandwidth
- Impedance matched
- Standard or precision types
- Low and medium power



Product configuration		
Interface	Gender	Standard
MMCX	plug (male)	HUBER+SUHNER - MMCX

Electrical data	
Impedance	50Ω
Operating frequency	0 GHz ... 6 GHz
VSWR	1.22
Return loss	20.1 dB

Electrical Data (frequency related)		
Frequency range	VSWR max	Return loss
0 GHz to 6 GHz	1.22	

Electrical Data (power)	
Average power	1 W at 85 °C ambient temperature. Linearly derated to W at 115 °C ambient temperature.
Electrical remarks	Standard spec for 1 Watt platform desing, samll interfaces, DOC-0000643688

Interface and material data		
Interface	MMCX / plug (male)	
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO / Gold Plating
Outer conductor	Brass	Gold Plating
Body	Brass	Gold Plating
Insulator	PFA / PTFE	

COAXIAL TERMINATION, 50 Ohm, MMCX, plug (male)

65_MMCX-50-0-2/111_N

Interface and material data

Piece parts	Material	Plating
-------------	----------	---------

Mechanical data

Weight	0.001 kg
--------	----------

Environmental data

Operation temperature	-40 °C ... 115°C
-----------------------	------------------

Ordering Information Table

Item number	Item description
85026661	65_MMCX-50-0-2/111_NE

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.

DOCUMENT PIM-P1770 / Date of publication: 09.11.2023 / uncontrolled copy