

COAXIAL TERMINATION, 50 Ohm, QMA, plug (male)

65_QMA-W50-0-5/113_N

Properties

- Various bandwidth
- Impedance matched
- Standard or precision types
- Low and medium power



Product configuration		
Interface	Gender	Standard
QMA	plug (male)	QMA QLF compliant

Electrical data	
Impedance	50Ω
Operating frequency	0 GHz ... 3 GHz
VSWR	1.2
Return loss	20.8 dB

Electrical Data (frequency related)		
Frequency range	VSWR max	Return loss
0 GHz to 1 GHz	1.09	
1 GHz to 3 GHz	1.2	

Electrical Data (power)	
Average power	1 W at 85 °C ambient temperature. Linearly derated to W at 115 °C ambient temperature.

Interface and material data		
Interface	QMA / plug (male)	
Piece parts	Material	Plating
Centre contact	Brass	SUCOPRO Plating
Outer conductor	Brass	SUCOPRO Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PTFE (Polytetrafluoroethylene)	
Gasket	VMQ (Silicone rubber)	

COAXIAL TERMINATION, 50 Ohm, QMA, plug (male)

65_QMA-W50-0-5/113_N

Interface and material data

Piece parts	Material	Plating
-------------	----------	---------

Mechanical data

Weight	0.0047 kg
--------	-----------

Environmental data

Operation temperature	-40 °C ... 115°C
Ingress protection (IP Rating)	IP68 (1 m, 24 h)

Ordering Information Table

Item number	Item description
84025816	65_QMA-W50-0-5/113_NE

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.

DOCUMENT PIM-P1756 / Date of publication: 09.11.2023 / uncontrolled copy