

**COAXIAL TERMINATION, 75 Ohm, TNC, plug (male)**

65\_TNC-75-0-1/133\_N

**Properties**

- Various bandwidth
- Impedance matched
- Standard or precision types
- Low and medium power



Product configuration		
Interface	Gender	Standard
TNC	plug (male)	IEC 60169-17_MIL-STD-348A/313_CECC 22200

Electrical data	
Impedance	75Ω
Operating frequency	0 GHz ... 1 GHz
VSWR	1.1
Return loss	26.4 dB

Electrical Data (power)	
Average power	1 W at 25 °C ambient temperature. Linearly derated to 0.6 W at 65 °C ambient temperature.
Peak power	500 W peak power

Interface and material data		
Interface	TNC / plug (male)	
<b>Piece parts</b>	<b>Material</b>	<b>Plating</b>
Centre contact	Bronze	Gold Plating
Outer conductor	Brass	Tri-metal Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	Tri-metal Plating
<b>Piece parts</b>	<b>Material</b>	<b>Plating</b>

Mechanical data	
Weight	0.02 kg

**COAXIAL TERMINATION, 75 Ohm, TNC, plug (male)**

65\_TNC-75-0-1/133\_N

Environmental data	
Operation temperature	-30 °C ... 65 °C

Ordering Information Table	
Item number	Item description
85218414	65_TNC-75-0-1/133_NE

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.

DOCUMENT PIM-P1742 / Date of publication: 28.11.2023 / uncontrolled copy