


COAXIAL CONNECTOR, MMCX, 50 Ohm, Straight cable plug (male)

11_MMCX-50-1-2/111_O

Properties

- Very small size
- Easy to connect and disconnect
- Wide range of board connectors and cable connectors available

**Product configuration**

Interface type	Gender	Standard
MMCX	plug	HUBER+SUHNER-MMCX

Interface and material data

Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer conductor	Brass	Gold Plating (without Nickel underplating)
Body	Brass	Gold Plating (without Nickel underplating)
Insulator	PFA / PTFE	
Crimp ferrule	Brass	Gold Plating (without Nickel underplating)

Electrical data

Impedance	50 Ω
Interface frequency	6 GHz

Mechanical data

Weight	0.0009 kg
Mating cycles	500
Cable entry centre contact	crimped
Cable entry outer contact	crimped

Environmental data

Operation temperature	-55 °C ... 155 °C
-----------------------	-------------------

COAXIAL CONNECTOR, MMCX, 50 Ohm, Straight cable plug (male)

11_MMCX-50-1-2/111_O

Ordering Information Table		
Item number	Item description	Packaging type
22645296	11_MMCX-50-1-2/111_OE	Single
84027753	11_MMCX-50-1-2/111_OH	Bulk 100 pcs

Suitable cables	
Cable group	U0 - 1 mm / 50 Ohm

Additional Information	
Only as assembly	No

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P38003 / Date of publication: 13.06.2024 / uncontrolled copy