

**COAXIAL CONNECTOR, N, 75 Ohm, Straight cable plug (male)**

11\_N-75-4-6/133\_N

**Properties**

- Screwed coupling mechanism for sturdy and reliable connection
- IP rating (interface, mated) IP67
- Interface dimensions according IEC/MIL



Product configuration		
Interface type	Gender	Standard
N	plug	IEC 60169-16_MIL-STD-348A/304_CECC 22210

Interface and material data		
Piece parts	Material	Plating
Centre contact	Brass	Gold Plating (Nickel underplated)
Outer conductor	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	

Electrical data	
Impedance	75 $\Omega$
Interface frequency	1.5 GHz

Mechanical data	
Weight	0.0336 kg
Mating cycles	500
Cable entry centre contact	soldered
Cable entry outer contact	clamped

Environmental data	
Operation temperature	-65 °C ... 165°C

**COAXIAL CONNECTOR, N, 75 Ohm, Straight cable plug (male)**

11\_N-75-4-6/133\_N

Ordering Information Table		
Item number	Item description	Packaging type
22542475	11_N-75-4-6/133_NE	Single

Suitable cables	
Cable group	X16 - 4 mm / 75 Ohm --- obsolete (integrated in U18)
	U18 - 4 mm / 75 Ohm
	U16 - 4 mm / 75 Ohm
Suitable cables	RG_59_B/U
	G_04233_D
	G_04133_D

Additional Information	
Only as assembly	No

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.  
DOCUMENT PIM-P3553 / Date of publication: 25.11.2023 / uncontrolled copy