

COAXIAL CONNECTOR, PC 1.85, 50 Ohm, Straight cable plug (male)

11_PC185-50-2-4/19-_NE

Properties

- Best electrical performance and excellent mechanical stability
- Extreme reliability
- Particularly well suited for semi-rigid, semi-flex and flexible cable
- Mechanical intermateable with PC 2.4

**Product configuration**

Interface type	Gender	Standard
PC 1.85	plug	IEC 61169-32

Interface and material data

Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO / Gold Plating
Outer conductor	Stainless Steel	Passivated (Plating)
Body	Stainless Steel	Passivated (Plating)
Insulator	LCP (Liquid crystal polymer)	
Coupling nut	Stainless Steel	Passivated (Plating)

Electrical data

Impedance	50 Ω
Interface frequency	67 GHz

Electrical Data (frequency related)

Frequency range	Return loss	VSWR
0 GHz ... 50 GHz	24 dB	1.135
50 GHz ... 67 GHz	20 dB	1.222

Mechanical data

Weight	0.0055 kg
Mating cycles	500
Cable entry centre contact	plugged
Cable entry outer contact	soldered

COAXIAL CONNECTOR, PC 1.85, 50 Ohm, Straight cable plug (male)

11_PC185-50-2-4/19-_NE

Environmental data	
Operation temperature	-40 °C ... 70°C

Ordering Information Table		
Item number	Item description	Packaging type
84144282	11_PC185-50-2-4/19-_NE	Single

Suitable cables	
Cable group	Y11 - 2 mm / 50 Ohm
Suitable cables	MULTIFLEX_86_HE

Additional Information	
Remarks	Extended temperature range to - 55°C .. +155°C if the taper sleeve 78_Z-0-2-1 (loose part, see outline drawing DOU-00235066) is not assembled.
Only as assembly	No

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/ EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P3544 / Date of publication: 25.11.2023 / uncontrolled copy