


COAXIAL CONNECTOR, SK, 50 Ohm, Straight cable plug (male)

11_SK-50-2-56/119_N

Properties

- The shortened male pin ensures a non-destructive mating process
- Particularly well suited for semi-rigid, semi-flex and flexible cable
- Mechanical intermateable with SMA and PC 3.5 (3.5 mm standard)



Product configuration		
Interface type	Gender	Standard
SK	plug	MIL-STD-348A/323

Interface and material data		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer conductor	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Body	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Insulator	PPE (Polyphenylene ether, PPO)	
Coupling nut	Stainless Steel	Passivated (Plating)
Gasket	VMQ (Silicone rubber)	

Electrical data	
Impedance	50 Ω
Interface frequency	40 GHz

Electrical Data (frequency related)		
Frequency range	Return loss	VSWR
0 GHz ... 40 GHz	20 dB	1.2

Mechanical data	
Weight	0.0023 kg
Mating cycles	500
Cable entry centre contact	soldered
Cable entry outer contact	soldered

COAXIAL CONNECTOR, SK, 50 Ohm, Straight cable plug (male)

11_SK-50-2-56/119_N

Environmental data		
Operation temperature	-40 °C ... 125°C	
Ordering Information Table		
Item number	Item description	Packaging type
84013230	11_SK-50-2-56/119_NE	Single
Suitable cables		
Cable group	Y3 - 2 mm / 50 Ohm	
	Y16 - 2 mm / 50 Ohm	
Suitable cables	SUCOFORM_86	
	SR_86_AL_TP_M17	
	SR_86_TP_M17	
Additional Information		
Only as assembly	No	

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P3493 / Date of publication: 25.11.2023 / uncontrolled copy