


**COAXIAL CONNECTOR, SMA, 50 Ohm, Straight cable plug (male)**

11\_SMA-50-3-235/133\_N

**Properties**

- Excellent return loss
- Intermateable with PC3.5 and SK
- Applicable in frequencies up to 18 GHz



Product configuration		
Interface type	Gender	Standard
SMA	plug	IEC 60169-15_MIL-STD-348A/310_CECC 22110

Interface and material data		
Piece parts	Material	Plating
Centre contact	Brass	SUCOPRO Plating
Outer conductor	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PTFE (Polytetrafluoroethylene)	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	

Electrical data	
Impedance	50 $\Omega$
Interface frequency	18 GHz

Electrical Data (frequency related)		
Frequency range	Return loss	VSWR
0 GHz ... 2.5 GHz	36 dB	1.03
2.5 GHz ... 5 GHz	35 dB	1.04
5 GHz ... 6 GHz	30 dB	1.07

Mechanical data	
Weight	0.0029 kg
Mating cycles	500
Cable entry centre contact	soldered
Cable entry outer contact	soldered

**COAXIAL CONNECTOR, SMA, 50 Ohm, Straight cable plug (male)**

11\_SMA-50-3-235/133\_N

Environmental data	
Operation temperature	-65 °C ... 165 °C

Ordering Information Table		
Item number	Item description	Packaging type
84130698	11_SMA-50-3-235/133_NE	Single
84104274	11_SMA-50-3-235/133_NP	Bulk 500 pcs

Suitable cables	
Cable group	Y17 - 3 mm / 50 Ohm
	Y12 - 3 mm / 50 Ohm
Suitable cables	SUCOFORM_141
	MULTIFLEX_141

Additional Information	
Only as assembly	No

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.  
DOCUMENT PIM-P3463 / Date of publication: 11.09.2024 / uncontrolled copy