

**COAXIAL CONNECTOR, SMA, 50 Ohm, Straight cable plug (male)**

11\_SMA-50-5-2/199\_N

**Properties**

- Excellent return loss
- Intermateable with PC3.5 and SK
- Applicable in frequencies up to 18 GHz



Product configuration		
Interface type	Gender	Standard
SMA	plug	IEC 60169-15_MIL-STD-348A/310_CECC 22110
Interface and material data		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Outer conductor	Stainless Steel	Passivated (Plating)
Body	Stainless Steel	Passivated (Plating)
Insulator	PFA / PTFE	
Coupling nut	Stainless Steel	
Gasket	VMQ (Silicone rubber)	
Electrical data		
Impedance	50 Ω	
Interface frequency	18 GHz	
Mechanical data		
Weight	0.0089 kg	
Mating cycles	500	
Cable entry centre contact	soldered	
Cable entry outer contact	clamped	
Environmental data		
Operation temperature	-65 °C ... 165°C	

**COAXIAL CONNECTOR, SMA, 50 Ohm, Straight cable plug (male)**

11\_SMA-50-5-2/199\_N

Ordering Information Table		
Item number	Item description	Packaging type
22643253	11_SMA-50-5-2/199_NE	Single

  

Suitable cables	
Cable group	Y7 - 5 mm / 50 Ohm
Suitable cables	SR_250_TP_M17

  

Additional Information	
Only as assembly	No

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.  
DOCUMENT PIM-P3434 / Date of publication: 25.11.2023 / uncontrolled copy