

COAXIAL CONNECTOR, SMA-reverse, 50 Ohm, Straight cable plug (male)

11_SMA-R50-4-97/133_N

Properties

- Excellent return loss
- Intermateable with PC3.5 and SK
- Applicable in frequencies up to 18 GHz



Product configuration		
Interface type	Gender	Standard
SMA-reverse	plug	HUBER+SUHNER-SMA-R50

Interface and material data		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer conductor	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	
Crimp ferrule	Copper	SUCOPLATE (R) Plating

Electrical data	
Impedance	50 Ω
Interface frequency	18 GHz

Electrical Data (frequency related)		
Frequency range	Return loss	VSWR
0.1 GHz ... 2 GHz	25 dB	1.119
2 GHz ... 4 GHz	20 dB	1.222
4 GHz ... 6 GHz	18 dB	1.288

Mechanical data	
Weight	0.007 kg
Mating cycles	500
Cable entry centre contact	soldered

COAXIAL CONNECTOR, SMA-reverse, 50 Ohm, Straight cable plug (male)

11_SMA-R50-4-97/133_N

Mechanical data		
Cable entry outer contact	crimped	
Environmental data		
Operation temperature	-65 °C ... 165°C	
Ordering Information Table		
Item number	Item description	Packaging type
84027004	11_SMA-R50-4-97/133_NH	Bulk 100 pcs
Suitable cables		
Cable group	X9 - 4 mm / 50 Ohm	
	X34 - 4 mm / 50 Ohm	
	X28 - 4 mm / 50 Ohm	
	S16 - 4 mm / 50 Ohm	
Suitable cables	SX_04172_B-60	
	SPUMA_240	
	Spuma_240-RS-FR	
Additional Information		
Remarks	Reverse polarised interface	
Only as assembly	No	

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P3427 / Date of publication: 25.11.2023 / uncontrolled copy