

SENCITY® OMNI-M stick antenna

1399.17.0231

Properties

- Omnidirectional stick antenna for Cellular bands between 790 MHz and 2690 MHz
- N female connector
- For both indoor and outdoor mounting with IP67 rating
- Gain of 3 dBi with vertical Polarisation
- L-bracket for pole or wall mounting scenario is included



Electrical bands		
	Band 1	Band 2
Frequency (MHz)	790 MHz ... 960 MHz	1710 MHz ... 2690 MHz
Impedance	50 Ω	50 Ω
VSWR	2	1.9
Gain (dBi)	2 dBi	3 dBi
Ambient Temperature	25 °C	
Composite Power max	25 W	

Ports	
Connector	N, jack (female)
Polarization	vertical

Connections	
Port number	

Mechanical data	
Weight	0.4 kg
Dimensions	263 mm x 32 mm (Height x Diameter)
Remarks	INCLUDED MOUNTING MATERIAL: Bracket 9091.99.0173 and 2 metal-bands for mast-diameter 25mm - 101mm, all piece parts made of stainless steel

SENCITY® OMNI-M stick antenna

1399.17.0231

Material data	
Radome material	Glass Fibre
Radome colour	RAL 9003 (signal white)


Environmental data	
Operation temperature	-40 °C ... 85°C
Storage temperature	-55 °C ... 85°C
Transport temperature	-40 °C ... 85°C
Environment (application)	Indoor/Outdoor
Ingress protection (IP Rating)	IP67

Environmental remarks
"LOW TEMPERATURE: IEC 60068-2-1; 72h; -55°C HIGH TEMPERATURE: IEC 60068-2-2; 72h; +85°C HUMIDITY: ETSI EN300-2-4 T4, 1E; 144h; 95% SALT SPRAY: EN 60068-2-11 / GB-T 10125; 96h MECHANICAL SHOCK: IEC 60721-3-4, 4M5 VIBRATION: IEC 60721-3-4; 30 min/axis; random; 4M5"

Additional Information
Mounting accessory included

SENCITY® OMNI-M stick antenna

1399.17.0231

Outline drawing

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/ EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P3254 / Date of publication: 31.10.2023 / uncontrolled copy