

**RG179 LSFH, 75 Ohm, 3 GHz, 105°C, ø2.54 mm, RADOX® jacket**

ENVIROFLEX\_179

**Properties**

- Halogen free alternative to RG cables
- Low smoke
- Ozone, UV and weathering resistance
- UL AWM style 3651



<b>Construction</b>			
Component	Material	Detail	Diameter
Centre conductor	Steel, Copper + Silver plated	Strand-07	0.305 mm
Dielectric	SPEX (Crosslink Foam PE)		1.55 mm
Outer conductor	Copper, Silver plated	Braid, 94%	2 mm
Outer conductor			
Jacket	RADOX	RAL 5015 - bl	2.54 mm +/- 0.07 mm

<b>Electrical data</b>	
Impedance	75 Ω +/- 3Ω
Operating frequency	≤ 3 GHz
Capacitance	63 pF/m
Velocity of signal propagation	70 %
Signal delay	4.78 ns/m
Screening effectiveness	40 dB at frequency 0.01 GHz ... 1GHz
Insulation resistance	10000000 MΩ*m
Inner conductor resistance	747 Ω/km
Operating Voltage (at sea level)	≤ 1 kVrms
Voltage Rating UL	300 V
Phase vs temperature	8400 ppm at temperature -40 ... 100°C
Phase vs bending	0.7 °/GHz
Test voltage (50 Hz/1 min)	≤ 2 kVrms

<b>Mechanical data</b>	
Weight	approx. 11.1 g/m
Static bending radius	≥ 5 mm
Repeated bending radius	25 mm (bendings, up to 50)

**RG179 LSFH, 75 Ohm, 3 GHz, 105°C, ø2.54 mm, RADOX® jacket**

ENVIROFLEX\_179

Environmental data	
Operation temperature	-40 °C ... 105 °C
Installation temperature	-20 °C ... 60 °C
Flame propagation standard	UL 1581 § 1100
	IEC 60332-2
	EN 60332-1-2
Fire characteristics	free of halogenes, acc. standard IEC 60754
Smoke test	EN 61034-2
Ageing test	MIL-C-17 § 4.8.16
Cold bend test	MIL-C-17 § 4.8.19
UV resistance	IEC 60068-2-5, proc. C
Solar radiation	IEC 60068-2-5, proc. C

**Additional Information**

Railway certificates discontinued by end of 2017. Replacement type for railway: RADOX\_RF\_179.

**Suitable connectors**

Cable group	U5
-------------	----

**Ordering information**

Item number	Item description	Available as assembly only
23019104	ENVIROFLEX_179	No

**Power Matrix**

Calculation: typical Attenuation [ formula: (a\*f^0.5 + b\*f) ] and maximum Power CW [ formula: (p/f^0.5) ]

a coefficient typical =	<b>0.8288</b>	b coefficient typical =	<b>0.0725</b>
fmax =	<b>3</b>	P at 1 GHz =	<b>45</b>

Frequency GHz	Nom. attenuation (dB/m)	Nom. attenuation (dB/ft)	CW power (W)
	sea level 25°C ambient temperature	sea level 25°C ambient temperature	sea level 40°C ambient temperature
0.10	0.269	0.082	142
0.20	0.385	0.117	101
0.30	0.476	0.145	82
0.40	0.553	0.169	71
0.60	0.685	0.209	58
0.80	0.799	0.244	50
1.00	0.901	0.275	45
1.20	0.995	0.303	41
1.40	1.082	0.330	38
1.60	1.164	0.355	36
1.80	1.242	0.379	34
2.00	1.317	0.401	32
2.50	1.492	0.455	28
3.00	1.653	0.504	26

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.  
DOCUMENT PIM-P1120 / Date of publication: 12.08.2024 / uncontrolled copy