

**RG316, 50 Ohm, 3 GHz, 200°C, Ø2.5 mm, FEP jacket**

RG\_316\_/U

**Properties**

- Mil standard RG cable
- Excellent RF performance for precision applications
- Suitable for use in applications up to 3 GHz
- Extended temperature range



Construction			
Component	Material	Detail	Diameter
Centre conductor	Steel, Copper + Silver plated	Strand-07	0.54 mm
Dielectric	PTFE (Polytetrafluoroethylene)		1.55 mm
Outer conductor	Copper, Silver plated	Braid, 95%	2 mm
Jacket	FEP (Fluorinated ethylene propylene)	RAL 8015 - br	2.5 mm +/- 0.1 mm

Electrical data	
Impedance	50 Ω +/-2Ω
Operating frequency	≤ 3 GHz
Capacitance	97 pF/m
Velocity of signal propagation	69 %
Signal delay	4.86 ns/m
Screening effectiveness	38 dB at frequency 0.0001 GHz ... 1GHz
Insulation resistance	100000000 MΩ*m
Inner conductor resistance	235 Ω/km
Operating Voltage (at sea level)	≤ 1.5 kVrms
Test voltage (50 Hz/1 min)	≤ 3 kVrms

Mechanical data	
Weight	approx. 16 g/m
Static bending radius	≥ 15 mm
Repeated bending radius	25 mm
Dynamic bending radius	< 37.5 mm

**RG316, 50 Ohm, 3 GHz, 200°C, ø2.5 mm, FEP jacket**

RG\_316\_/U

Environmental data	
Operation temperature	-65 °C ... 200 °C
Installation temperature	-20 °C ... 60 °C
Flame propagation standard	IEC 60332-3
Fire characteristics	contains halogene

**Additional Information**

MIL reference: M17/113-RG316

**Suitable connectors**

Cable group U2

**Ordering information**

Item number	Item description	Available as assembly only
22510079	RG_316_/U	No

**Power Matrix**

Calculation: typical Attenuation [ formula: (a\*f^0.5 + b\*f) ] and maximum Power CW [ formula: (p/f^0.5) ]

a coefficient typical =	<b>0.7727</b>	b coefficient typical =	<b>0.0972</b>
fmax =	<b>3</b>	P at 1 GHz =	<b>135</b>

Frequency GHz	Nom. attenuation (dB/m) sea level 25°C ambient temperature	Nom. attenuation (dB/ft) sea level 25°C ambient temperature	CW power (W) sea level 40°C ambient temperature
0.20	0.365	0.111	302
0.40	0.528	0.161	213
0.60	0.657	0.200	174
0.80	0.769	0.234	151
1.00	0.870	0.265	135
1.20	0.963	0.294	123
1.40	1.050	0.320	114
1.60	1.133	0.345	107
1.80	1.212	0.369	101
2.00	1.287	0.392	95
3.00	1.630	0.497	78

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.  
DOCUMENT PIM-P959 / Date of publication: 08.08.2024 / uncontrolled copy