

Coaxial Cable RG_59_B/U

Description

PE-75 Ohm - single screen



Technical Data

Construction

	Material	Detail	Diameter
Centre conductor	Steel, Copper plated	Wire	0.58 mm
Dielectric	PE (Polyethylene)		3.64 mm
Outer conductor	Copper	Braid, 93%	4.5 mm
Jacket	PVC II (low migration)	RAL 9005 - bk	6.1 mm +/- 0.15

Print: HUBER+SUHNER RG 59 B/U 75 Ohm (PA no.)

Electrical Data

Impedance	75 Ω +/- 1.5
Operating Frequency	1 GHz
Capacitance	67 pF/m
Velocity of signal propagation	66 %
Signal delay	5.07 ns/m
Insulation resistance	≥ 1 x 10 ⁸ MQm
Min. screening effectiveness	≥ 40 dB (up to 1 GHz)
Max. operating voltage	≤ 3 kV _{rms} (at sea level)
Test voltage	6 kV _{rms} (50 Hz/1 min)

Mechanical Data

Weight		5 kg/100 m
Min. bending radius	static	35 mm
	repeated (for ≤ 50 bendings)	65 mm

Environmental Data

Temperature range	-25 °C... +85 °C
Installation temperature	-20 °C... +60 °C
2011/95/EC (RoHS)	compliant

Additional Information

Ordering Information

Order as RG_59_B/U

Remarks

(For details refer to the HUBER+SUHNER RF CABLES GENERAL CATALOGUE or contact your nearest HUBER+SUHNER partner)

Suitable Connectors

Cable group U16 4 mm / 75 Ohm

Coaxial Cable RG_59_B/U

Matrix typical Attenuation [formula: $(a \cdot f^{0.5} + b \cdot f)$] and maximum Power CW [formula: $(p/f^{0.5})$]

Coefficients:

a = 0.3173

b = 0.0499

f_{max} = 1

P at 1GHz = 101

Frequency (GHz)	Nom. attenuation (dB / m) sea level 25° C ambient temperature	Nom. attenuation (dB / ft) sea level 25° C ambient temperature	Max. CW power (watt) sea level 40° C ambient temperature
0.05	0.07	0.022	452
0.1	0.11	0.032	319
0.15	0.13	0.040	261
0.2	0.15	0.046	226
0.25	0.17	0.052	202
0.3	0.19	0.058	184
0.35	0.21	0.063	171
0.4	0.22	0.067	160
0.45	0.24	0.072	151
0.5	0.25	0.076	143
0.55	0.26	0.080	136
0.6	0.28	0.084	130
0.65	0.29	0.088	125
0.7	0.3	0.092	121
0.75	0.31	0.095	117
0.8	0.32	0.099	113
0.85	0.33	0.102	110
0.9	0.35	0.105	106
0.95	0.36	0.109	104
1.0	0.37	0.112	101