

Coaxial Cable SPUMA_240-FR-01

Description

PE Foam - 50 Ohm - double screened



Technical Data

Construction

	Material	Detail	Diameter
Centre conductor	Copper	Wire	1.42 mm
Dielectric	SPE (Foamed Polyethylene)		3.82 mm
Outer conductor	Aluminum / PES	longitudinal Foil, 100%	3.94 mm
Outer conductor	Copper, Tin plated	Braid, 94 %	4.52 mm
Jacket	LSFH (modified polyethylene)	RAL 9005 - bk	6.17 mm +/- 0.1

Print: HUBER+SUHNER SPUMA 240-FR-01 50 Ohm (PA no.)

Electrical Data

Impedance	50 Ω +/- 2
Operating Frequency	6 GHz
Capacitance	78.9 pF/m
Velocity of signal propagation	82.6 %
Signal delay	4.05 ns/m
Insulation resistance	≥ 1 x 10 ⁶ MΩm
Min. screening effectiveness	≥ 90 dB (up to 6 GHz)
Max. operating voltage	≤ 0.9 kV _{rms} (at sea level)
Test voltage	1.5 kV _{rms} (50 Hz/1 min)

Mechanical Data

Weight		6.1 kg/100 m
Min. bending radius	static	14 mm
	repeated (for ≤ 50 bendings)	53 mm

Environmental Data

Temperature range	-40 °C... +85 °C
Installation temperature	-20 °C... +60 °C
Flammability	IEC 60332-1, IEC 60332-3-25,
Smoke density	EN 61034-2
Halogen test	IEC 60754
Uv resistance test	ISO 4892-2A
2011/95/EC (RoHS)	compliant

Additional Information

EN 45545 compliant hazard level for indoor cables: HL3

DIN 5510-2, NF F 16-101 and NFPA-130 compliant

Ordering Information

Order as SPUMA_240-FR-01

Remarks

(For details refer to the HUBER+SUHNER RF CABLES GENERAL CATALOGUE or contact your nearest HUBER+SUHNER partner)

Suitable Connectors

Cable group X28 4 mm / 50 Ohm

Coaxial Cable SPUMA_240-FR-01

Matrix typical Attenuation [formula: $(a \cdot f^{0.5} + b \cdot f)$] and maximum Power CW [formula: $(p/f^{0.5})$]

Coefficients:

a = 0.25984

b = 0.00926

f_{max} = 6

P at 1GHz = 260

Frequency (GHz)	Nom. attenuation (dB / m) sea level 25° C ambient temperature	Nom. attenuation (dB / ft) sea level 25° C ambient temperature	Max. CW power (watt) sea level 40° C ambient temperature
0,3	0,15	0,044	475
0,6	0,21	0,063	336
0,9	0,25	0,078	274
1,2	0,3	0,090	237
1,5	0,33	0,101	212
1,8	0,37	0,111	194
2,1	0,4	0,121	179
2,4	0,42	0,129	168
2,7	0,45	0,138	158
3,0	0,48	0,146	150
3,3	0,5	0,153	143
3,6	0,53	0,160	137
3,9	0,55	0,167	132
4,2	0,57	0,174	127
4,5	0,59	0,181	123
4,8	0,61	0,187	119
5,1	0,63	0,193	115
5,4	0,65	0,199	112
5,7	0,67	0,205	109
6,0	0,69	0,211	106