

Coaxial Cable SUCOFEED_1_5/8_LW_LA

Description

Corrugated coaxial cable - low weight - low attenuation



Technical Data

Construction

	Material	Detail	Diameter
Centre conductor	Copper	Tube (c)	typ. 17.6 mm
Dielectric	SPE (Foamed Polyethylene)		typ. 41.4 mm
Outer conductor	Aluminium	Tube (c)100%	typ. 46.5 mm
Jacket	PE-LD (Low-density polyethylene)	RAL 9011 - graphite black	50 mm +/- 0.6

Print: HUBER+SUHNER_SUCOFEED_1_5/8_LW_LA_#batch-number#_#metric-length#

Electrical Data

Impedance	50 Ω +/- 1
Operating Frequency	≤ 2.75 GHz
Capacitance	typ. 74 pF/m
Inductance	typ. 0.19 μH/m
Velocity of signal propagation	typ. 89 %
Signal delay	typ. 3.8 ns/m
Insulation resistance	≥ 3 x 10 ⁶ MΩm
Screening effectiveness	≥ 120 dB
Operating voltage	≤ 5.6 kVrms (at sea level)
Test voltage	11 kVrms (50 Hz/1 min)
Outer conductor resistance DC	≤ 0.95 Ω/km
Inner conductor resistance DC	≤ 1.1 Ω/km

Mechanical Data

Weight		≤ 1020 kg/100 m
Bending Radius	static	≥ 300 mm
Bending Radius	repeated (for ≤ 15 bendings)	≥ 500 mm
Tensile strength		≤ 2000 N
Bending force moment		≤ 46 Nm

Environmental Data

Temperature range	-55 °C... +85 °C
Installation temperature	-40 °C... +60 °C
Halogen test	IEC 60754-1
2011/65/EU (RoHS)	compliant

Additional Information

Remarks

(For details contact your nearest HUBER+SUHNER partner)

Suitable Connectors

Cable group M42 42 mm / 50 Ohm

Suitable Tools

Suitable Grounding Kit

Cable grounding kit 9076.99.N158 9076.99.P158

Coaxial Cable SUCOFEEED_1_5/8_LW_LA

Matrix typical Attenuation [formula: $(a \cdot f^{0.5} + b \cdot f)$] and maximum Power CW [formula: $(p/f^{0.5})$]

Coefficients:

a = 0.0217174 typ.

b = 0.00310892 typ.

f_{max.} = 2.75

P ≤ at 1GHz = 4410

Frequency (GHz)	Nom. attenuation (dB / 100 m) sea level 20° C ambient temperature	Nom. attenuation (dB / 100 ft) sea level 20° C ambient temperature	Max. CW power (watt) sea level 40° C ambient temperature
0.100	0.72	0.22	13946
0.150	0.89	0.27	11387
0.200	1.03	0.31	9861
0.400	1.50	0.46	6973
0.450	1.60	0.49	6574
0.500	1.69	0.52	6237
0.700	2.03	0.62	5271
0.800	2.19	0.67	4931
0.900	2.34	0.71	4649
1.000	2.48	0.76	4410
1.500	3.13	0.95	3601
1.700	3.36	1.02	3382
1.800	3.47	1.06	3287
2.000	3.69	1.13	3118
2.200	3.91	1.19	2973
2.500	4.21	1.28	2789
3.000	4.69	1.43	2546

Matrix typical Return Loss

Frequency Range (MHz)	Frequency Range (MHz)	Frequency Range (MHz)	Frequency Range (MHz)
380 to 470	806 to 960	1710 to 2200	5 to 2700
typ. 28.4 dB	typ. 25.1 dB	typ. 25.1 dB	typ. 20 dB